



# 2025 CATALOG



LIMITED WARRANTY  
**7 YEARS** COMPRESSOR  
**5 YEARS** PARTS



WE ARE READY!  
Watch Video





## COOPER&HUNTER

With more than 25 years of experience in air conditioning and ventilation, Cooper&Hunter has grown into a leading HVAC market player. The brand is dedicated to technological innovation and consumer-driven product development, generating HVAC equipment that adheres to the highest quality standards, providing reliable, energy-efficient, and cost-effective air conditioning solutions.


While products under the Cooper&Hunter brand are distributed in more than 55 countries worldwide, the brand's growth within the US market has been rapid. Cooper&Hunter stands out from big-name brands by providing quality support to customers and technicians alike, with their in-house technical support team offering troubleshooting and warranty support Monday through Friday from 9am to 5pm in 5 different languages (including English, Spanish, Mandarin, Russian, and Ukrainian).



© 03.2025 All rights reserved.

## COOPER&HUNTER SPONSORSHIPS

Cooper&Hunter is proud to sponsor the New York Yankees, NASCAR, Florida Panthers, and Miami Zoo because these partnerships reflect our commitment to excellence, innovation, and community engagement. The New York Yankees represent a storied legacy of success and ambition, while NASCAR embodies the thrill of speed and precision engineering—both values we share. Supporting the Florida Panthers aligns with our dedication to teamwork and perseverance, and our partnership with the Miami Zoo highlights our commitment to environmental sustainability and education. Together, these sponsorships allow us to connect with diverse audiences, celebrate shared values, and foster a sense of community across different arenas.



### Florida Panthers Celebrate Victory!

Once again, Cooper&Hunter has re-newed our Sponsorship Agreement with the Florida Panthers. Just Recently, after a 30-year journey, the Panthers finally etched their name in hockey history, avoiding a collapse after losing three consecutive games. The Florida Panthers clinched their first-ever Stanley Cup title! In a thrilling Game 7 showdown against the Edmonton Oilers, the Panthers secured a hard-fought 2-1 victory.




### HVAC Meets High-Octane!

We are thrilled to continue our sponsorship with MBM Motorsports, a team we deeply admire and respect for their achievements and values. Supporting **Chad Finchum**, an HVAC Technician, Client, and Nascar Driver, who has consistently demonstrated his skills and talent in the sport, is a source of pride for us. We believe this partnership perfectly represents the synergy between HVAC excellence and NASCAR speed.




### Home Run Collaboration!

Cooper&Hunter is thrilled to announce our renewed sponsorship of the New York Yankees! They did an outstanding job in 2024, winning the East and American leagues again. We are confident that this partnership will continue to thrive in 2025. Our collaboration with the Yankees aligns perfectly with our brand's values of striving for excellence and innovation. We look forward to supporting the team in their future endeavors and continuing to engage with the community through this prestigious partnership.



### Chilling with Nature!

Cooper&Hunter is proud to sponsor the Miami Zoo Foundation, the non-profit partner of Zoo Miami. This sponsorship aligns with Cooper&Hunter's mission to support wildlife conservation, environmental sustainability, and community engagement. Additionally, as HVAC experts, Cooper&Hunter has provided Astoria units for optimal climate control in various animal habitats, ensuring a comfortable and healthy environment for the animals.




# Making Hot Rooms Cool And Cold Rooms Cozy



## CONTENT

<b>Single-Zone</b>	7
Unit Match-Up Guides	8-9
Astoria Pro	10
Astoria	14
Olivia	16
Olivia Midnight	18
Mia NY	20
Ceiling Cassette	22
One Way Cassette	24
Mini Floor Console	26
Universal Floor Ceiling	28
Slim Duct	30
Multi-Position Air Handler	34
PEAQ	36
<b>Multi-Zone Regular and Hyper Series</b>	40
Multi-Zone Combination Charts	56-59
<b>Monoblock</b>	61
PTAC Unit	62
Accessories	64
AHRI Certifications	65

# HYPER and REGULAR Series



*The newest generation of outdoor units now provide a wide range of compatibility across Cooper&Hunter's vast product selection to better serve any project configuration.*

**SINGLE-ZONE**

## UNIT MATCH-UPS REGULAR

Btu/h	Astoria Astoria Pro	Olivia	Olivia Midnight	Ceiling Cassette Ceiling Cassette Pro	One-Way Cassette	Slim Duct	Mini Console	Floor Ceiling	Multi-Position Air Handler
6K	 CH-RES06-115VO	CH-R060LVWM-115VI							
9K	 CH-RES09-115VO	CH-R090LVWM-115VI	CH-RB090LVWM-115VI						
12K	 CH-RES12-115VO	CH-R120LVWM-115VI	CH-RB120LVWM-115VI						
9K	 CH-RES09-230VO	CH-R09MASTWM-230VI CH-PRO09MASTWM-230VI	CH-R09MOLVWM-230VI CH-RB09MOLVWM-230VI	CH-RH09MCT CH-RSH09-12MCT (Dip Switch for 9K)	CH-RSH06-12MCT1W (Dip Switch for 9K)	CH-RS09MDT-MS CH-RS06-12MDT-MS (Dip Switch for 9K)	CH-RSH09MMC		
12K	 CH-RES12-230VO	CH-RH12MASTWM-230VI CH-PRO12MASTWM-230VI	CH-R12MOLVWM-230VI CH-RB12MOLVWM-230VI	CH-RH12MCT CH-RSH09-12MCT (Dip Switch for 12K)	CH-RSH06-12MCT1W (Dip Switch for 12K)	CH-RS12MDT-MS CH-RS06-12MDT-MS (Dip Switch for 12K)	CH-RSH12MMC		
18K	 CH-RES18-230VO	CH-RH18MASTWM-230VI CH-PRO18MASTWM-230VI	CH-R18MOLVWM-230VI CH-RB18MOLVWM-230VI	CH-RH18MCT CH-RSH18MCT	CH-RSH18MCT1W	CH-RS18MDT-MS	CH-RSH16MMC	CH-RSH18MFC	CH-RS18MAHU
24K	 CH-RES24-230VO	CH-RH24MASTWM-230VI CH-PRO24MASTWM-230VI	CH-R24MOLVWM-230VI CH-RB24MOLVWM-230VI	CH-RH24MCT CH-RSH24MCT		CH-RS24MDT-HS		CH-RSH24MFC	CH-RS24MAHU
30K	 CH-REL30-230VO	CH-RH30MASTWM-230VI CH-PRO30MASTWM-230VI	CH-R30MELVWM-230VI						CH-RS30MAHU
36K	 CH-REL36-230VO	CH-RH36MASTWM-230VI CH-PRO36MASTWM-230VI	CH-R36MELVWM-230VI						
36K	 CH-R36LCU-230VO			CH-RH36LCCT CH-RSH36LCCT		CH-RS36LCDT-HS		CH-RSH36LCFC	CH-RS36LCAHU
48K	 CH-R48LCU-230VO			CH-RH48LCCT CH-RSH48LCCT		CH-RS48LCDT-HS		CH-RSH48LCFC	CH-RS48LCAHU
60K	 CH-R60LCU-230VO					CH-RS60LCDT-HS		CH-RSH60LCFC	CH-RS60LCAHU

## UNIT MATCH-UPS HYPER

Btu/h	Astoria Astoria Pro	Olivia	Olivia Midnight	Ceiling Cassette Ceiling Cassette Pro	One-Way Cassette	Slim Duct	New Console	Floor Ceiling	Multi-Position Air Handler
6K	 CH-RHP06F9-230VO	CH-RH06MASTWM-230VI CH-PRO06MASTWM-230VI	CH-R06MOLVWM-230VI	CH-RB06MOLVWM-230VI	CH-RSH06-12MCT1W (Dip Switch for 6K)	CH-RS06MDT-MS CH-RS06-12MDT-MS (Dip Switch for 6K)			
9K	 CH-RHP09-230VO	CH-RH09MASTWM-230VI CH-PRO09MASTWM-230VI	CH-R09MOLVWM-230VI	CH-RB09MOLVWM-230VI	CH-RH09MCT CH-RSH09-12MCT (Dip Switch for 9K)	CH-RS09MDT-MS CH-RS06-12MDT-MS (Dip Switch for 9K)	CH-RSH09MMC		
12K	 CH-RHP12-230VO	CH-RH12MASTWM-230VI CH-PRO12MASTWM-230VI	CH-R12MOLVWM-230VI	CH-RB12MOLVWM-230VI	CH-RH12MCT CH-RSH09-12MCT (Dip Switch for 12K)	CH-RS12MDT-MS CH-RS06-12MDT-MS (Dip Switch for 12K)	CH-RSH12MMC		
15K	 CH-RHP15-230VO	CH-RH15MASTWM-230VI CH-PRO15MASTWM-230VI							
18K	 CH-RHP18-230VO	CH-RH18MASTWM-230VI CH-PRO18MASTWM-230VI	CH-R18MOLVWM-230VI	CH-RB18MOLVWM-230VI	CH-RH18MCT CH-RSH18MCT	CH-RS18MDT-MS	CH-RSH16MMC	CH-RSH18MFC	CH-RS18MAHU
24K	 CH-RHP24-230VO	CH-RH24MASTWM-230VI CH-PRO24MASTWM-230VI	CH-R24MOLVWM-230VI	CH-RB24MOLVWM-230VI	CH-RH24MCT CH-RSH24MCT			CH-RSH24MFC	CH-RS24MAHU
33K	 CH-RHP33-230VO	CH-RH33HASTWM-230VI CH-PRO33HASTWM-230VI	CH-RH33HELVWM-230VI						
36K	 CH-RHP36LCU-230VO			CH-RH36LCCT CH-RSH36LCCT		CH-RS36LCDT-HS		CH-RSH36LCFC	CH-RS36LCAHU
48K	 CH-RHP48LCU-230VO			CH-RH48LCCT CH-RSH48LCCT		CH-RS48LCDT-HS		CH-RSH48LCFC	CH-RS48LCAHU
60K	 CH-RHP60LCU-230VO					CH-RS60LCDT-HS		CH-RSH60LCFC	CH-RS60LCAHU




# A PROFESSIONAL UNIT MADE FOR PROFESSIONALS



6K, 9K, 12K, 15K, 18K, 24K,  
30K, 33K, 36K Btu/h

- E-Box and PCB located in the front of the unit with a cover kickstand providing easy access.
- Revolutionary design offers convenient disassembly & maintenance with an easy-to-remove blower wheel.
- Included Refrigerant Sensor and Humidity Sensor.
- Larger air inlet/outlet for improved air flow.
- Auto-Swing for vertical and horizontal louvers.
- Easy to remove magnetic filter on top.
- Compatible with regular (-13°F) or Hyper (-22°F) outdoor units.
- Self-Cleaning function (Single-Zone only).
- Follow Me mode.
- Eco Mode (Single-Zone only).
- 46° Freeze Protection.



WATCH OUR  
INFORMATIONAL  
VIDEO



DOWNLOAD THE  
COOPER&HUNTER  
REMOTE APP



cooperandhunter.us | TECHNICAL SUPPORT 786-953-6706



**INDOOR**

Indoor Model			CH-PRO06MASTWM-230VI	CH-PRO09MASTWM-230VI	CH-PRO12MASTWM-230VI	CH-PRO15MASTWM-230VI	CH-PRO18MASTWM-230VI	CH-PRO24MASTWM-230VI	CH-PRO33MASTWM-230VI	CH-PRO09MASTWM-230VI	CH-PRO12MASTWM-230VI	CH-PRO18MASTWM-230VI	CH-PRO24MASTWM-230VI	CH-PRO30MASTWM-230VI	CH-PRO36MASTWM-230VI
Power Supply	Rated	V, Ph, Hz	208/230,60,1	208/230,60,1	208/230,60,1	208/230,1, 60	208/230,60,1	208/230,60,1	208/230,60,1	208/230,60,1	208/230,60,1	208/230,60,1	208/230,60,1	208/230,60,1	208/230,60,1
	Rated Capacity	Cooling	Btu/h	6,000	9,000	12,000	15,400	18,000	24,000	33,000	9,000	12,000	18,000	24,000	30,000
Heating		Btu/h	7,000	12,000	12,000	15,400	18,000	29,000	36,000	10,000	12,000	18,000	25,000	30,000	36,000
Minimum Circuit Ampacity (MCA)		A	3	3	3	3	3	3	3	3	3	3	3	3	3
Max. Fuse		A	15	15	15	15	15	15	15	15	15	15	15	15	15
Indoor Air Flow (Turbo/Hi/Mi/L0/Si)		CFM	382.6/323.7/229.6/176.6/147.2	441.4/323.7/229.6/176.6/147.2	441.4/323.7/229.6/176.6/147.2	635.7/500.3/359.0/294.3 / /	635.7/500.3/359.0/294.3 / /	812.3/618.0/412.0/317.8 / -	865.2/735.8/600.4/423.8 / -	441.4/323.7/229.6/176.6/147.2	441.4 / 323.7 / 229.6 / 176.6 / 147.2	635.7/500.3/359.0/294.3 / -	812.3/618.0/412.0/317.8 / -	882.9/635.7/506.2/382.6 / -	882.9/635.7/506.2/382.6 / -
Indoor Noise Level (Turbo/Hi/Mi/L0/Si)		dB(A)	44.0/36.5/32.5/22.0/19.5	N/A/38/33/20.5/19.5	47/36.5/32.5/22/19.5	49.5/45.0/38.0/31.5/19.5	49.5/45.0/38.0/31.5/19.5	54.5/43.5/38.5/27/16	57.0/53.0/46.5/35.5/29.5	47.5/43/31/18/17	46/38/33.0/18.0/18	49/45/39/28/20	51.5/43.5/39.5/21.5/19	53.0/45.5/40/30.5/19.5	N/A/49/43.5/34.5/31.5
Indoor	Dimension (WxDxH)	inch	33.74x9.09x11.81	33.74x9.09x11.81	33.74x9.09x11.81	40.31x9.69x12.64	40.31x9.69x12.64	47.13x11.02x14.61	47.13x11.02x14.61	33.74x9.09x11.81	33.74 x 9.09 x 11.81	40.31x9.69x12.64	47.13x11.02x14.61	47.13x11.02x14.61	47.13x11.02x14.61
	Packing (WxDxH)	inch	36.22x12.20x14.57	36.22x12.20x14.57	36.22x12.20x14.57	43.11x12.80x15.75	43.11x12.80x15.75	50.39x14.17x17.91	50.39x14.17x17.91	36.22x12.20x14.57	36.22x12.20x14.57	43.11x12.80x15.75	50.39x14.17x17.91	50.39x14.17x17.91	50.39x14.17x17.91
	Net/Gross Weight	lbs.	22.93/29.32	23.37/29.98	22.93/29.32	27.34/36.60	27.34/36.60	43.65/55.56	43.21/55.78	23.37/29.98	22.93/29.32	27.34/36.60	43.65/55.56	43.21/54.67	43.21/54.67
Room Temperature	Cooling	F	60-90	60-90	60-90	60-90	60-90	60-90	60-90	60-90	60-90	60-90	60-90	60-90	60-90
	Heating	F	32-86	32-86	32-86	32-86	32-86	32-86	32-86	32-86	32-86	32-86	32-86	32-86	32-86
Liquid Side/Gas Side		Inch	1/4"/3/8"	1/4"/3/8"	1/4"/3/8"	1/4" / 1/2"	1/4"/1/2"	3/8"/5/8"	3/8"/3/4"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 1/2"	3/8" / 5/8"	3/8" / 5/8"	3/8" / 5/8"



**HYPER**


**REGULAR**

**ENTRY LEVEL**



**OUTDOOR**

Outdoor Model			CH-RHP06F9-230VO	CH-RHP09-230VO	CH-RHP12-230VO	CH-RHP15-230VO	CH-RHP18-230VO	CH-RHP24-230VO	CH-RHP33-230VO	CH-RES09-230VO	CH-RES12-230VO	CH-RES18-230VO	CH-RES24-230VO	CH-REL30-230VO	CH-REL36-230VO
Power Supply	Rated	V, Ph, Hz	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,60,1	208/230,60,1	208/230,60,1	208/230,60,1	208/230,60,1	208/230,60,1
	Voltage Range	V	187-253	187-253	187-253	187-253	187-253	187-253	187-253	187-253	187-253	187-253	187-253	187-253	187-253
Cooling	Rated Capacity (range)	Btu/h	2,300-12,600	3,800-13,500	3,800-14,600	8,800-19,400	8,800-19,400	12,600-27,900	15,000-37,000	2200-13000	2900-14500	3500-18900	5500-29500	6500-32800	6600-36800
	Rated Current	A	3.1	4.1	4.0	7.1	6.4	8.3	12.7	4.5	4.1	6.3	7.4	11.2	18.0
	EER2		18.0	15.4	13.4	13.5	12.5	13.0	12.0	14.9	13.0	12.7	14	12	8.6
	SEER2		25.5	27.4	25.4	22.2	21.4	21	19.5	25.8	25.5	23.5	23	20.5	19.0
Heating	Rated Capacity (range)	Btu/h	3,000-11,000	3,800-16,000	3,800-16,000	11,200-19,500	11,200-19,500	11,800-29,700	19,700-37,800	4,100-13,800	4,500-15,400	7,700-21,000	9,900-30,800	12,600-31,400	9,600-38,000
	Rated current	A	4.0	4.1	4.1	8.5	7.2	11.0	13.7	3.3	4.0	6.7	8.3	13.1	16.2
	COP	W/W	4.20	3.76	3.76	3.5	3.26	3.42	3.37	3.90	3.90	3.50	3.96	3.08	2.85
	HSPF4		14.8	12.5	10.5	11.5	11.0	13.5	10.5	12.5	10.6	10.8	11.7	9.5	8.5
	HSPF5		11.5	9.5	8.0	8.5	8.5	9.8	8.6	9.2	8.0	8.0	8.7	7.2	6.6
Heating at 17°F (AHRI)	Rated capacity	Btu/h	9,200	12,800	12,800	19,200	19,200	25,000	30,200	9,400	9,600	14,900	19,300	21,500	24,200
Heating at 5°F (-15°C)	Rated capacity	Btu/h	7,700	11,500	11,500	17,500	18,000	24,200	35,000	8,000	8,400	12,800	19,600	20,000	22,000
	COP	W/W	2.39	1.80	1.80	1.83	1.92	2.34	1.98	2.36	2.30	2.10	2.54	2.03	1.90
Minimum Circuit Ampacity		A	12.0	15.0	15.0	19	19.0	24.9	34.0	12	12	18	24	28	33
Max.Fuse (Outdoor Unit)		A	15	15	15	20	20	25	35	15	15	20	25	30	35
Outdoor Air Flow (Max.)		CFM	1,235.3	1,470.6	1,470.6	1764.7	1,764.7	2,235.3	2,235.3	1235.3	1235.3	1764.7	2235.3	2235.3	2235.3
Outdoor Noise Level (Sound Pressure)		dB(A)	53	56	56	59	59	61.5	63.5	52.5	56	58	58	61	63
Dimension (WxDxH)		inch	30.12x11.93x21.85	31.69x12.99x21.81	31.69x12.99x21.81	35.04x13.46x26.50	35.04x13.46x26.50	37.24x16.14x31.89	37.24x16.14x31.89	30.12x11.93x21.85	30.12x11.93x21.85	35.04x13.46x26.50	37.24x16.14x31.89	37.24x16.14x31.89	37.24x16.14x31.89
Packing (WxDxH)		inch	34.92x13.27x24.02	36.02x14.57x24.21	36.02x14.57x24.21	39.17x15.67x29.13	39.17x15.67x29.13	42.91x19.68x34.84	42.91x19.68x34.84	34.92x13.27x24.02	34.92x13.27x24.02	39.17x15.67x29.13	42.91x19.68x34.84	42.91x19.68x34.84	42.91x19.68x34.84
Net/Gross Weight		lbs.	62.17/67.68	72.75/78.70	72.75/78.70	99.87/107.80	99.87/107.80	130.29/141.31	156.97/167.99	62.17/67.68	62.17/67.68	92.59/100.31	122.13/132.28	142.86/154.54	150.35/160.27
Refrigerant Type / Charge		oz.	R454B / 32.45	R454B / 35.27	R454B / 35.27	R454B/55.38	R454B / 55.38	R454B / 63.49	R454B / 87.13	R454B/ 32.45	R454B/ 32.45	R454B/ 47.97	R454B/ 70.55	R454B / 84.66	R454B / 112.88
Refrigerant Precharge Length		ft.	25	25	25	25	25	25	25	25	25	25	25	25	
Additional Charge for Each ft.		oz/ft	0.16	0.16	0.16	0.16	0.16	0.32	0.32	0.16	0.16	0.16	0.32	0.32	
Design Pressure		PSIG	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340
Refrigerant Piping Liquid Side/Gas Side		inch	1/4"/3/8"	1/4"/3/8"	1/4"/3/8"	1/4" / 1/2"	1/4"/1/2"	3/8"/5/8"	3/8"/3/4"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 1/2"	3/8" / 5/8"	3/8" / 5/8"	3/8" / 5/8"
Max. Pipe Length		ft.	82	82	82	98.4	98.4	164	164	82	82	98.40	164	164	213.20
Max. Difference in Level		ft.	49.20	49.20	49.20	65.60	65.60	82	82	49.2	49.2	65.6	82	82	98.4
Ambient Temperature	Cooling	°F	-22-122	-22-122	-22-122	-22-122	-22-122	-22-122	-22-122	-13-122	-13-122	-13-122	-13-122	-13-122	-13-122
	Heating	°F	-22-75	-22-75	-22-75	-22-75	-22-75	-22-75	-22-75	-13-75	-13-75	-13-75	-13-75	-13-75	-13-75
Certifications	ETL		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	AHRI		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Energy Star for Cold Climates		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	NEEP		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓



- CONTROL OPTIONS**
- Smart Kit Included with Downloadable C&H app
  - Remote Control Included
  - 12V Wall Thermostat (Purchased Separately)





**INDOOR**

Indoor Model			CH-RH06MASTWM-230VI	CH-RH09MASTWM-230VI	CH-RH12MASTWM-230VI	CH-RH15MASTWM-230VI	CH-RH18MASTWM-230VI	CH-RH24MASTWM-230VI	CH-RH33MASTWM-230VI	CH-RH09MASTWM-230VI	CH-RH12MASTWM-230VI	CH-RH18MASTWM-230VI	CH-RH24MASTWM-230VI	CH-RH30MASTWM-230VI	CH-RH36MASTWM-230VI
Power Supply	Rated	V, Ph, Hz	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60
	Rated Capacity	Btu/h	6,000	9,000	12,000	15,400	18,000	24,000	33,000	9,000	12,000	18,000	24,000	30,000	6,600-36,800
Minimum Circuit Ampacity (MCA)		A	3	3	3	3	3	3	3	3	3	3	3	3	3
Max. Fuse		A	15	15	15	15	15	15	15	15	15	15	15	15	15
Indoor Air Flow (Turbo/Hi/Mi/Lo/Si)		CFM	382.6/323.7/229.6/176.6/147.2	441.4/323.7/229.6/176.6/147.2	441.4/323.7/229.6/176.6/147.2	635.7/500.3/359.0/294.3 / /	635.7/500.3/359.0/294.3 / /	812.3/618.0/412.0/317.8 / /	865.2/735.8/600.4/423.8 / /	441.4/323.7/229.6/176.6 / 147.2	441.4/323.7/229.6/176.6 / 147.2	635.7/500.3/359.0/294.3 / /	812.3/618.0/412.0/317.8 / /	882.9/635.7/506.2/382.6 / /	882.9/635.7/506.2/382.6/323.7
Indoor Noise Level (Turbo/Hi/Mi/Lo/Si)		dB(A)	44.0/36.5/32.5/22.0/19.5	N/A/38/33/20.5/19.5	47/36.5/32.5/22/19.5	49.5/45.0/38.0/31.5/19.5	49.5/45.0/38.0/31.5/19.5	54.5/43.5/38.5/27/16	57.0/53.0/46.5/35.5/29.5	47.5/43/31/18/17	46/38/33.0/18.0/18	49/45/39/28/20	51.5/43.5/39.5/21.5/19	53.0/45.5/40/30.5/19.5	N/A/49/43.5/34.5/31.5
Indoor	Dimension (WxDxH)	inch	33.74x9.09x11.81	33.74x9.09x11.81	33.74x9.09x11.81	40.31x9.69x12.64	40.31x9.69x12.64	47.13x11.02x14.61	47.13x11.02x14.61	33.74x9.09x11.81	33.74x9.09x11.81	40.31x9.69x12.64	47.13x11.02x14.61	47.13x11.02x14.61	47.13x11.02x14.61
	Packing (WxDxH)	inch	36.22x12.20x14.57	36.22x12.20x14.57	36.22x12.20x14.57	43.11x12.80x15.75	43.11x12.80x15.75	50.39x14.17x17.91	50.39x14.17x17.91	36.22x12.20x14.57	36.22x12.20x14.57	43.11x12.80x15.75	50.39x14.17x17.91	50.39x14.17x17.91	50.39x14.17x17.91
	Net/Gross Weight	lbs.	22.93/29.32	23.37/29.98	22.93/29.32	27.34/36.60	27.34/36.60	43.65/55.56	43.21/55.78	23.37/29.98	22.93/29.32	27.34/36.60	43.65/55.56	43.21/55.67	43.21/54.67
Room Temperature	Cooling	F	60-90	60-90	60-90	60-90	60-90	60-90	60-90	60-90	60-90	60-90	60-90	60-90	60-90
	Heating	F	32-86	32-86	32-86	32-86	32-86	32-86	32-86	32-86	32-86	32-86	32-86	32-86	32-86
Liquid Side/Gas Side		Inch	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 1/2"	1/4" / 1/2"	3/8" / 5/8"	3/8" / 3/4"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 1/2"	3/8" / 5/8"	3/8" / 5/8"	3/8" / 5/8"



**HYPER**

**REGULAR**

**ENTRY LEVEL**

**OUTDOOR**

Outdoor Model			CH-RHP06F9-230VO	CH-RHP09-230VO	CH-RHP12-230VO	CH-RHP15-230VO	CH-RHP18-230VO	CH-RHP24-230VO	CH-RHP33-230VO	CH-RES09-230VO	CH-RES12-230VO	CH-RES18-230VO	CH-RES24-230VO	CH-RES30-230VO	CH-RES36-230VO
Power Supply	Rated	V, Ph, Hz	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60
	Voltage Range	V	187-253	187-253	187-253	187-253	187-253	187-253	187-253	187-253	187-253	187-253	187-253	187-253	187-253
Cooling	Rated Capacity (range)	Btu/h	2,300-12,600	3,800-13,500	3,800-14,600	8,800-19,400	8,800-19,400	12,600-27,900	15,000-37,000	2,200-13,000	2,900-14,500	3,500-18,900	5,500-29,500	6,500-32,800	6,600-36,800
	Rated Current	A	3.1	4.1	4.0	7.1	6.4	8.3	12.7	4.5	4.1	6.3	7.4	11.2	18.0
	EER2		18	15.4	13.4	13.5	12.5	13	12	14.9	13	12.7	14	12	8.6
	SEER2		25.5	27.4	25.4	22.2	21.4	21	19.5	25.8	25.5	23.5	23	20.5	19
Heating at 47°F	Rated Capacity (range)	Btu/h	3,000-11,000	3,800-16,000	3,800-16,000	11,200-19,500	11,200-19,500	11,800-29,700	19,700-37,800	4,100-13,800	4,500-15,400	7,700-21,000	9,900-30,800	12,600-31,400	9,600-38,000
	Rated current	A	4.0	4.1	4.1	8.5	7.2	11.0	13.7	3.3	4.0	6.7	8.3	13.1	16.2
	COP	W/W	4.20	3.76	3.76	3.5	3.26	3.42	3.37	3.90	3.90	3.50	3.96	3.08	2.85
	HSPF4		14.8	12.5	10.5	11.5	11.0	13.5	10.5	12.5	10.6	10.8	11.7	9.5	8.5
	HSPF5		11.5	9.5	8.0	8.5	8.5	9.8	8.6	9.2	8.0	8.0	8.7	7.2	6.6
Heating at 17°F (AHR)	Rated capacity	Btu/h	9,200	12,800	12,800	19,200	19,200	25,000	30,200	9,400	9,600	14,900	19,300	21,500	24,200
Heating at 5°F (-15°C)	Rated capacity	Btu/h	7,700	11,500	11,500	17,500	18,000	24,200	35,000	8,000	8,400	12,800	19,600	20,000	22,000
Minimum Circuit Ampacity		A	12	15	15	19	19	24.9	34	12	12	18	24	28	33
Max.Fuse (Outdoor Unit)		A	15	15	15	20	20	25	35	15	15	20	25	30	35
Outdoor Air Flow (Max.)		CFM	1235.3	1470.6	1470.6	1764.7	1764.7	2235.3	2235.3	1235.3	1235.3	1764.7	2235.3	2235.3	2235.3
Outdoor Noise Level (Sound Pressure)		dB(A)	53	56	56	59	59	61.5	63.5	52.5	56	58	58	61	63
Outdoor	Dimension (WxDxH)	inch	30.12x11.93x21.85	31.69x12.99x21.81	31.69x12.99x21.81	35.04x13.46x26.50	35.04x13.46x26.50	37.24x16.14x31.89	37.24x16.14x31.89	30.12x11.93x21.85	30.12x11.93x21.85	35.04x13.46x26.50	37.24x16.14x31.89	37.24x16.14x31.89	37.24x16.14x31.89
	Packing (WxDxH)	inch	34.92x13.27x24.02	36.02x14.57x24.21	36.02x14.57x24.21	39.17x15.67x29.13	39.17x15.67x29.13	42.91x19.68x34.84	42.91x19.68x34.84	34.92x13.27x24.02	34.92x13.27x24.02	39.17x15.67x29.13	42.91x19.68x34.84	42.91x19.68x34.84	42.91x19.68x34.84
	Net/Gross Weight	lbs.	62.17/67.68	72.75/78.70	72.75/78.70	99.87/107.80	99.87/107.80	130.29/141.31	156.97/167.99	62.17/67.68	62.17/67.68	92.59/100.31	122.13/132.28	142.86/154.54	150.35/160.27
Refrigerant Type / Charge		oz.	R454B/32.45	R454B/35.27	R454B/35.27	R454B/55.38	R454B/55.38	R454B/63.49	R454B/87.13	R454B/32.45	R454B/32.45	R454B/47.97	R454B/ 70.55	R454B/84.66	R454B/112.88
Refrigerant Precharge Length		ft.	25	25	25	25	25	25	25	25	25	25	25	25	
Additional Charge for Each ft.		oz/ft	0.16	0.16	0.16	0.16	0.16	0.32	0.32	0.16	0.16	0.16	0.32	0.32	
Design Pressure		PSIG	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340	
Refrigerant Piping Liquid Side/Gas Side		inch	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 1/2"	1/4" / 1/2"	3/8" / 5/8"	3/8" / 3/4"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 1/2"	3/8" / 5/8"	3/8" / 5/8"	3/8" / 5/8"
Max. Pipe Length		ft.	82	82	82	98.4	98.4	164	164	82	82	98.4	164	164	213.2
Max. Difference in Level		ft.	32.8	32.8	32.8	65.60	66	82	82	49.2	49.2	65.6	82	82	98.4
Ambient Temperature	Cooling	°F	-22-122	-22-122	-22-122	-22-122	-22-122	-22-122	-22-122	-13-122	-13-122	-13-122	-13-122	-13-122	-13-122
	Heating	°F	-22-75	-22-75	-22-75	-22-75	-22-75	-22-75	-22-75	-13-75	-13-75	-13-75	-13-75	-13-75	-13-75
Certifications	ETL		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	AHRI		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Energy Star for Cold Climate		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	NEEP		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓



Humidity Sensor



**CONTROL OPTIONS**

- Smart Kit Included with Downloadable C&H app
- Remote Control Included
- 12V Wall Thermostat (Purchased Separately)





### CONTROL OPTIONS

- Smart Kit Included with Downloadable C&H app
- Remote Control Included
- 12V Wall Thermostat (Purchased Separately)



INDOOR	Indoor Model		CH-R06MOLVWM-230VI	CH-R09MOLVWM-230VI	CH-R12MOLVWM-230VI	CH-R18MOLVWM-230VI	CH-R24MOLVWM-230VI	CH-R33HELVWM-230VI	CH-R06OLVWM-115VI	CH-R09OLVWM-115VI	CH-R12OLVWM-115VI	CH-R09MOLVWM-230VI	CH-R12MOLVWM-230VI	CH-R18MOLVWM-230VI	CH-R24MOLVWM-230VI	CH-R30MOLVWM-230VI	CH-R36MOLVWM-230VI	
	Power Supply	Rated	V, Ph, Hz	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	115V, 1, 60	115, 1, 60	115, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60
	Rated Capacity	Btu/h	6,000	9,000	12,000	18,000	23,000	33,000	7,000	9,000	12,000	9,000	12,000	18,000	24,000	30,000	36,000	
	Minimum Circuit Ampacity (MCA)	A	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	
	Max. Fuse	A	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	
	Indoor Air Flow (Turbo/Hi/Mi/Lo/Si)	CFM	294.3/235.4/176.6/141.3/N/A	382.6/294.3/194.2/153.0/N/A	382.6/294.3/194.2/153.0/-	759.3/500.3/441.4/370.8/-	759.3/588.6/459.1/382.6/-	829.9/676.9/529.7/447.3/-	370.8/306.1/235.4/188.4/141.3	370.8/306.1/235.4/188.4/141.3	370.8/306.1/235.4/188.4/141.3	382.6/294.3/194.2/153.0/N/A	382.6/294.3/194.2/153.0//	759.3/500.3/441.4/370.8//	759.3/588.6/459.1/382.6//	871.1/647.5/447.3/329.6//	871.1/676.9/447.3/329.6//	
	Indoor Noise Level (Turbo/Hi/Mi/Lo/Si)	dB(A)	42.0/37.0/32.0/24.0	N/A/39.5/33/24	N/A/42/35.5/22.5	54.5/45.0/40.0/24.5	54.5/49.5/43.5/34.5	56.0/52.5/46.5/29.5	44.0/40.5/35.0/26.5/17.5	44.0/40.5/35.0/26.5/17.5	44.0/40.5/35.0/26.5/17.5	45.5/42/36/21/19.5	46/43/37/20/19	54/45/40.0/26/20	54.0/48.5/43.5/27.5/20.5	56.5/52/45/36/22	57.0/51.0/45.0/33.5/27.5	
Indoor	Dimension (WxDxH)	inch	28.70x7.87x11.50	31.57x7.87x11.61	31.57x7.87x11.61	42.60x9.21x13.27	42.60x9.21x13.27	49.57x11.14x14.25	31.57x7.87x11.61	31.57x7.87x11.61	31.57x7.87x11.61	31.57x7.87x11.61	31.57x7.87x11.61	31.57x7.87x11.61	42.64x9.61x13.23	42.60x9.21x13.27	49.57x11.14x14.25	49.57x11.14x14.25
	Packing (WxDxH)	inch	31.10x10.63x14.76	34.45x11.22x14.96	34.45x11.22x14.96	45.47x12.40x16.34	45.47x12.40x16.34	52.76x15.16x17.72	34.45x11.22x14.96	34.45x11.22x14.96	34.45x11.22x14.96	34.45x11.22x14.96	34.45x11.22x14.96	34.45x11.22x14.96	45.47x12.40x16.34	45.47x12.40x16.34	52.76x15.16x17.72	52.76x15.16x17.72
	Net/Gross Weight	lbs.	17.64/23.15	18.96/24.25	18.96/24.25	30.42/39.68	30.86/40.56	43.21/57.32	18.96/24.47	18.96/24.47	18.96/24.47	18.96/24.47	18.96/24.25	18.74/24.25	30.42/39.68	30.86/40.56	43.43/56.88	43.43/56.88
Room temperature	Cooling	°F	60 - 90	60 - 90	60 - 90	60 - 90	60 - 90	60 - 90	60 - 90	60 - 90	60 - 90	60 - 90	60 - 90	60 - 90	60 - 90	60 - 90	60 - 90	60 - 90
	Heating	°F	32 - 86	32 - 86	32 - 86	32 - 86	32 - 86	32 - 86	32 - 86	32 - 86	32 - 86	32 - 86	32 - 86	32 - 86	32 - 86	32 - 86	32 - 86	32 - 86
	Liquid Side/Gas Side	Inch	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 1/2"	3/8" / 5/8"	3/8" / 3/4"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 1/2"	3/8" / 5/8"	3/8" / 5/8"	3/8" / 5/8"

### HYPER

### REGULAR

### ENTRY LEVEL

OUTDOOR	Outdoor Model		CH-RHP06F9-230VO	CH-RHP09-230VO	CH-RHP12-230VO	CH-RHP18-230VO	CH-RHP24-230VO	CH-RHP33-230VO	CH-RES06-115VO	CH-RES09-115VO	CH-RES12-115VO	CH-RES09-230VO	CH-RES12-230VO	CH-RES18-230VO	CH-RES24-230VO	CH-REL30-230VO	CH-REL36-230VO
	Power Supply	Rated	V, Ph, Hz	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	115, 1, 60	115, 1, 60	115, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60
	Voltage Range	V	187-253	187-253	187-253	187-253	187-253	187-253	103.5-126.5	103.5-126.5	103.5-126.5	187-253	187-253	187-253	187-253	187-253	187-253
Cooling	Rated Capacity (range)	Btu/h	2,500-11,500	3,600-13,500	3,600-13,500	8,400-20,200	16,800-24,500	15,000-35,900	2,600-13,000	2,600-13,000	3,100-10,900	2,600-13,000	2,600-13,700	3,600-20,000	9,700-27,000	6,800-33,900	6,600-36,800
	Rated Current	A	3.1	4.0	4.1	9.0	8.4	12.6	6.9	6.9	10.0	4.6	4.5	6.0	8.0	11.0	17.0
	EER2		16.0	15.0	13.2	13.0	12.5	11.7	15.0	15.0	12.5	14.7	12.2	13.5	13.0	12.0	9.3
	SEER2		25.3	26.0	24.0	21.7	22.3	20.0	24.5	24.5	23.2	24.6	23.1	24.0	23.5	22.3	19.5
Heating at 47°F	Rated Capacity (range)	Btu/h	3,200-10,700	3,800-16,000	3,800-16,000	10,300-23,000	11,800-28,100	19,900-38,200	4,500-12,800	4,500-12,800	45,00-12,800	4,200-14,200	4,100-14,400	7,600-22,000	11,300-32,700	12,300-32,100	11,400-44,000
	Rated current	A	4.0	4.3	4.3	9.5	11.2	14.1	7.6	7.6	10.3	3.6	4.3	6.2	10.4	12.6	16.0
	COP	W/W	3.80	3.63	3.63	3.54	3.05	3.22	4.20	4.20	3.70	3.66	3.69	3.81	3.08	3.03	2.95
	HSPF4		14.6	12.5	10.5	10.8	13.3	10.5	10.7	10.7	10.4	13.0	11.5	11.1	10.0	9.0	9.1
	HSPF5		11.2	10.1	8.0	8.8	9.6	8.6	8.2	8.2	7.6	9.5	8.5	8.3	7.7	7.0	7.0
Heating at 17°F (AHRI)	Rated capacity	Btu/h	8,600	12,800	12,800	19,800	24,400	30,200	8,600	8,900	10,200	8,900	9,900	14,500	21,300	21,500	25,600
	Minimum Circuit Ampacity	A	12	15	15	19	24.9	34	18	18	18	12	12	18	24	28	33
	Max. Fuse (Outdoor Unit)	A	15	15	15	20	25	35	20	20	20	15	15	20	25	30	35
	Outdoor Air Flow (Max.)	CFM	1,235.3	1,470.6	1,470.6	1,764.7	2,235.3	2,235.3	1,235.3	1,235.3	1,235.3	1,235.3	1,235.3	1,764.7	2,235.3	2,235.3	2,235.3
	Outdoor Noise Level (Sound Pressure)	dB(A)	53.0	56.0	56.0	59.0	61.0	63.5	53.0	53.0	53.0	52.5	54.0	59.0	60.0	61.5	63.0
	Dimension (WxDxH)	inch	30.12x11.93x21.85	31.69x12.99x21.81	31.69x12.99x21.81	35.04x13.46x26.50	37.24x16.14x31.89	37.24x16.14x31.89	30.12x11.93x21.85	30.12x11.93x21.85	30.12x11.93x21.85	30.12x11.93x21.85	30.12x11.93x21.85	35.04x13.46x26.50	37.24x16.14x31.89	37.24x16.14x31.89	37.24x16.14x31.89
	Packing (WxDxH)	inch	34.92x13.27x24.02	36.02x14.57x24.21	36.02x14.57x24.21	39.17x15.67x29.13	42.91x19.69x34.84	42.91x19.69x34.84	34.92x13.27x24.02	34.92x13.27x24.02	34.92x13.27x24.02	34.92x13.27x24.02	34.92x13.27x24.02	39.17x15.67x29.13	42.91x19.69x34.84	42.91x19.69x34.84	42.91x19.69x34.84
	Net/Gross Weight	lbs.	62.17/67.68	72.75/78.70	72.75/78.70	99.87/107.80	130.29/141.31	156.97/167.99	64.59/70.11	64.59/70.11	64.59/70.11	62.17/67.68	62.17/67.68	92.59/100.31	122.13/132.28	142.86/154.54	150.35/160.27
	Refrigerant Type / Charge	oz.	R454B/32.45	R454B/35.27	R454B/35.27	R454B/55.38	R454B/63.49	R454B/87.13	R454B/33.51	R454B/33.51	R454B/33.51	R454B/32.45	R454B/32.45	R454B/47.97	R454B/70.55	R454B/84.66	R454B/112.88
	Refrigerant Precharge Length	ft.	25	25	25	25	25	25	25	25	25	25	25	25	25	25	
	Additional Charge for Each ft.	oz/ft	0.16	0.16	0.16	0.16	0.32	0.32	0.16	0.16	0.16	0.16	0.16	0.16	0.32	0.32	
	Design Pressure	PSIG	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340
	Refrigerant Piping Liquid Side/Gas Side	inch	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 1/2"	3/8" / 5/8"	3/8" / 3/4"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 1/2"	3/8" / 5/8"	3/8" / 5/8"
	Max. Pipe Length	ft.	82	82	82	98.4	164	164	82	82	82	82	82	98.4	164	164	213.2
	Max. Difference in Level	ft.	49.2	49.2	49.2	65.6	82	82	49.2	49.2	49.2	49.2	49.2	65.6	82	82	98.4
Ambient Temperature	Cooling	°F	-22-122	-22-122	-22-122	-22-122	-22-122	-22-122	-13-122	-13-122	-13-122	-13-122	-13-122	-13-122	-13-122	-13-122	-13-122
	Heating	°F	-22-75	-22-75	-22-75	-22-75	-22-75	-22-75	-13-75	-13-75	-13-75	-13-75	-13-75	-13-75	-13-75	-13-75	-13-75
Certifications	ETL		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	AHRI		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Energy Star for Cold Climate		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	NEEP		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓




INDOOR			CH-RB06MOLVWM-230VI	CH-RB09MOLVWM-230VI	CH-RB12MOLVWM-230VI	CH-RB18MOLVWM-230VI	CH-RB24MOLVWM-230VI	CH-RB090LVWM-115VI	CH-RB120LVWM-115VI	CH-RB09MOLVWM-230VI	CH-RB12MOLVWM-230VI	CH-RB18MOLVWM-230VI	CH-RB24MOLVWM-230VI
Power Supply	Rated	V, Ph, Hz	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	115, 1, 60	115, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60
	Rated Capacity	Btu/h	6,000	9,000	12,000	18,000	23,000	9,000	12,000	9,000	12,000	18,000	24,000
Minimum Circuit Ampacity (MCA)		A	3	3	3	3	3	3	3	3	3	3	3
Max. Fuse		A	15	15	15	15	15	15	15	15	15	15	15
Indoor Air Flow (Turbo/Hi/Mi/Lo/Si)		CFM	294.3/235.4/176.6/141.3/VA	382.6/294.3/194.2/153.0/N/A	382.6/294.3/194.2/153.0//	759.3/500.3/441.4/ 370.8 //	759.3/588.6/459.1/ 382.6 //	370.8/306.1/235.4/188.4/141.3	370.8/306.1/235.4/188.4/141.3	382.6/294.3/194.2/153.0/ N/A	382.6/294.3/194.2/153.0//	759.3/500.3/441.4/ 370.8 //	759.3/588.6/459.1/382.6 //
Indoor Noise Level (Turbo/Hi/Mi/Lo/Si)		dB(A)	42/37/32/24/20	N/A/39.5/33/24/20.5	N/A/42/35.5/22.5/20	54.5/45/40/24.5/20	54.5/49.5/43.5/34.5/20.5	44.0/40.5/35.0/26.5/17.5	44.0/40.5/35.0/26.5/17.5	45.5/42/36/21/19.5	46/43/37/20/19	54/45/40.0/26/20	54.0/48.5/43.5/27.5/20.5
Indoor	Dimension (WxDxH)	inch	28.70x7.87x11.50	31.57x7.87x11.61	31.57x7.87x11.61	42.60x9.21x13.27	42.60x9.21x13.27	31.57x7.87x11.61	31.57x7.87x11.61	31.57x7.87x11.61	31.57x7.87x11.61	42.64x9.61x13.23	42.60x9.21x13.27
	Packing (WxDxH)	inch	31.10x10.63x14.76	34.45x11.22x14.96	34.45x11.22x14.96	45.47x12.40x16.34	45.47x12.40x16.34	34.45x11.22x14.96	34.45x11.22x14.96	34.45x11.22x14.96	34.45x11.22x14.96	45.47x12.40x16.34	45.47x12.40x16.34
	Net/Gross Weight	lbs.	17.64/23.15	18.96/24.25	18.96/24.25	30.42/39.68	30.86/40.56	18.96/24.47	18.96/24.47	18.96/24.25	18.74/24.25	30.42/39.68	30.86/40.56
Room temperature	Cooling	°F	60 - 90	60 - 90	60 - 90	60 - 90	60 - 90	60 - 90	60 - 90	60 - 90	60 - 90	60 - 90	60 - 90
	Heating	°F	32 - 86	32 - 86	32 - 86	32 - 86	32 - 86	32 - 86	32 - 86	32 - 86	32 - 86	32 - 86	32 - 86
Liquid Side/Gas Side		Inch	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 1/2"	3/8" / 5/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 1/2"	3/8" / 5/8"

OUTDOOR			HYPER					REGULAR					
Outdoor Model			CH-RHP06F9-230VO	CH-RHP09-230VO	CH-RHP12-230VO	CH-RHP18-230VO	CH-RHP24-230VO	CH-RES09-115VO	CH-RES12-115VO	CH-RES09-230VO	CH-RES12-230VO	CH-RES18-230VO	CH-RES24-230VO
Power Supply	Rated	V, Ph, Hz	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	115, 1, 60	115, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60
	Voltage Range	V	187-253	187-253	187-253	187-253	187-253	103.5-126.5	103.5-126.5	187-253	187-253	187-253	187-253
Cooling	Rated Capacity (range)	Btu/h	2,500-11,500	3,600-13,500	3,600-13,500	8,400-20,200	16,800-24,500	2,600-13,000	3,100-10,900	2,600-13,000	2,600-13,700	3,600-20,000	9,700-27,000
	Rated Current	A	3.1	4.0	4.1	9.0	8.4	6.9	10.0	4.6	4.5	6.0	8.0
	EER2		16.0	15.0	13.2	13.0	12.5	15.0	12.5	14.7	12.2	13.5	13.0
	SEER2		25.3	26.0	24.0	21.7	22.3	24.5	23.2	24.6	23.1	24.0	23.5
Heating at 47°F	Rated Capacity (range)	Btu/h	3,200-10,700	3,800-16,000	3,800-16,000	10,300-23,000	11,800-28,100	4,500-12,800	45,00-12,800	4,200-14,200	4,100-14,400	7,600-22,000	11,300-32,700
	Rated current	A	4.0	4.3	4.3	9.5	11.2	7.6	10.3	3.6	4.3	6.2	10.4
	COP	W/W	3.80	3.63	3.63	3.54	3.05	4.20	3.70	3.66	3.69	3.81	3.08
	HSPF4		14.6	12.5	10.5	10.8	13.3	10.7	10.4	13.0	11.5	11.1	10.0
	HSPF5		11.2	10.1	8.0	8.8	9.6	8.2	7.6	9.5	8.5	8.3	7.7
Heating at 17°F (AHRI)	Rated capacity	Btu/h	8,600	12,800	12,800	19,800	24,400	8,900	10,200	8,900	9,900	14,500	21,300
Minimum Circuit Ampacity		A	12	15	15	19	24.9	18	18	12	12	18	24
Max. Fuse (Outdoor Unit)		A	15	15	15	20	25	20	20	15	15	20	25
Outdoor Air Flow (Max.)		CFM	1,235.3	1,470.6	1,470.6	1,764.7	2,235.3	1,235.3	1,235.3	1,235.3	1,235.3	1,764.7	2,235.3
Outdoor Noise Level (Sound Pressure)		dB(A)	53.0	56.0	56.0	59.0	61.0	53.0	53.0	52.5	54.0	59.0	60.0
Dimension (WxDxH)		inch	30.12x11.93x21.85	31.69x12.99x21.81	31.69x12.99x21.81	35.04x13.46x26.50	37.24x16.14x31.89	30.12x11.93x21.85	30.12x11.93x21.85	30.12x11.93x21.85	30.12x11.93x21.85	35.04x13.46x26.50	37.24x16.14x31.89
Packing (WxDxH)		inch	34.92x13.27x24.02	36.02x14.57x24.21	36.02x14.57x24.21	39.17x15.67x29.13	42.91x19.69x34.84	34.92x13.27x24.02	34.92x13.27x24.02	34.92x13.27x24.02	34.92x13.27x24.02	39.17x15.67x29.13	42.91x19.69x34.84
Net/Gross Weight		lbs.	62.17/67.68	72.75/78.70	72.75/78.70	99.87/107.80	130.29/141.31	64.59/70.11	64.59/70.11	62.17/67.68	62.17/67.68	92.59/100.31	122.13/132.28
Refrigerant Type / Charge		oz.	R454B/32.45	R454B/35.27	R454B/35.27	R454B/55.38	R454B/63.49	R454B/33.51	R454B/33.51	R454B/32.45	R454B/32.45	R454B/47.97	R454B/70.55
Refrigerant Precharge Length		ft.	25	25	25	25	25	25	25	25	25	25	
Additional Charge for Each ft.		oz/ft	0.16	0.16	0.16	0.16	0.32	0.16	0.16	0.16	0.16	0.32	
Design Pressure		PSIG	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340	
Refrigerant Piping Liquid Side/Gas Side		inch	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 1/2"	3/8" / 5/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 1/2"	3/8" / 5/8"
Max. Pipe Length		ft.	82	82	82	98.4	164	82	82	82	82	98.4	164
Max. Difference in Level		ft.	49.2	49.2	49.2	65.6	82	49.2	49.2	49.2	49.2	65.6	82
Ambient Temperature	Cooling	°F	-22-122	-22-122	-22-122	-22-122	-22-122	-13-122	-13-122	-13-122	-13-122	-13-122	-13-122
	Heating	°F	-22-75	-22-75	-22-75	-22-75	-22-75	-13-75	-13-75	-13-75	-13-75	-13-75	-13-75
Certifications	ETL		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	AHRI		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Energy Star for Cold Climate		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	NEEP		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓



**CONTROL OPTIONS**

- Smart Kit Included with Downloadable C&H app
- Remote Control Included
- 12V Wall Thermostat (Purchased Separately)



**CONTROL OPTIONS**

- Smart Kit Included with Downloadable C&H app
- Remote Control Included
- 12V Wall Thermostat (Purchased Separately)



**FEATURES**

- Sleek matte finish
- Inverter Technology
- Turbo Function
- Smart Kit Included
- Silent Function
- LED Display
- Auto Swing (horizontal louvers)
- Comfortable Sleep Mode
- Multiple Fan Speeds
- Self-Cleaning Function
- Follow Me Function
- Line Set, Communication Cable (16 ft.) and Drain Pipe
- One to One, Single-Zone Only



INDOOR			CH-RLS06MIA-115VI	CH-RLS09MIA-115VI	CH-RLS12MIA-115VI	CH-RLS09MIA-230VI	CH-RLS12MIA-230VI	CH-RLS18MIA-230VI	CH-RLS24MIA-230VI
Power Supply	Rated	V, Ph, Hz	115, 1, 60	115, 1, 60	115, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60
	Rated Capacity	Cooling	Btu/h	6,000	9,000	12,000	9,000	12,000	18,000
Heating		Btu/h	7,000	10,000	12,000	10,000	12,000	18,800	24,000
Minimum Circuit Ampacity (MCA)	A		3	3	3	3	3	3	3
Max. Fuse	A		15	15	15	15	15	15	15
Indoor Air Flow (Turbo/Hi/Mi/Lo/Si)	CFM		282.5/235.4/206.0/164.8/117.7	282.5/235.4/206.0/164.8/117.7	341.4/309.0/206.0/176.6/94.2	312.0/264.9/194.2/153.0/105.9	359.0/306.1/206.0/144.2/77.8	429.7/388.5/259.0/217.8/115.5	729.9/529.7/400.2/329.6/177.5
	Indoor Noise Level (Turbo/Hi/Mi/Lo/Si)	dB(A)	43.0/37.5/33.5/25.0/18.0	43.0/37.5/33.5/25.0/18.0	45.0/40.5/32.5/25.0/17.5	40.5/35.5/31.5/23.0/18.5	40.5/35.5/31.5/23.0/18.5	40.5/35.5/31.5/23.0/18.5	54.0/45.0/41.5/27.0/21.5
Indoor	Dimension (WxDxH)	inch	28.43x7.36x11.42	28.43x7.36x11.42	31.57x7.44x11.69	28.43x7.36x11.42	31.57x7.44x11.69	37.99x8.46x12.56	42.52x8.90x13.19
	Packing (WxDxH)	inch	31.10x10.63x14.76	31.10x10.63x14.76	34.45x11.22x14.96	31.10x10.63x14.76	34.45x11.22x14.96	41.14x12.01x16.14	45.47x16.34x12.60
	Net/Gross Weight	lbs.	17.42/22.93	17.42/22.93	19.40/25.13	16.98/22.27	19.40/25.13	24.47/32.63	30.64/39.46
Room Temperature	Cooling	°F	60-90	60-90	60-90	60-90	60-90	60-90	60-90
	Heating	°F	32-86	32-86	32-86	32-86	32-86	32-86	32-86
Liquid Side/Gas Side	inch		1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 1/2"	3/8" / 5/8"

OUTDOOR			CH-RLS06MIA-115VO	CH-RLS09MIA-115VO	CH-RLS12MIA-115VO	CH-RLS09MIA-230VO	CH-RLS12MIA-230VO	CH-RLS18MIA-230VO	CH-RLS24MIA-230VO
Power Supply	Rated	V, Ph, Hz	115, 1, 60	115, 1, 60	115, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60
	Voltage Range	V	103.5-126.5	103.5-126.5	103.5-126.5	187-253	187-253	187-253	187-253
Cooling	Rated Capacity Range	Btu/h	2,200-9,900	2,200-9,900	2,200-12,300	2,300-9,700	1,700-13,300	4,100-19,000	5,500-24,200
	Rated Current	A	8.0	8.0	12.7	5.0	5.0	7.2	10.9
	EER2		12.5	12.5	10.1	12.6	10.8	10.8	10.0
	SEER2		21.5	21.5	21.2	21.2	21.3	19.2	18.7
	SEER2		21.5	21.5	21.2	21.2	21.3	19.2	18.7
Heating at 47°F	Rated Capacity Range	Btu/h	4,200-10,200	4,200-10,200	3,400-12,200	4,300-11,100	3,500-13,400	6,200-20,200	6,300-27,000
	Rated current	A	9.8	9.8	11.7	4.0	4.9	8.1	9.6
	COP	W/W	3.29	3.29	3.30	3.20	3.18	3.06	3.31
	HSPF4		9	9	8.7	9.1	9.1	9.6	9.3
	HSPF5		7	7	6.7	7	7	7.5	7.3
Minimum Circuit Ampacity	A		18	18	19	12	13	15	19
Max. Fuse (Outdoor Unit)	A		20	20	20	15	15	20	20
Outdoor Air Flow (Max.)	CFM		1,294.1	1,294.1	1,235.3	1,294.1	1,235.3	1,235.3	1,764.7
Outdoor Noise Level (Sound Pressure)	dB(A)		52.5	52.5	54	53.5	54	56	59.5
Dimension (WxDxH)	inch		30.12x11.93x21.85	30.12x11.93x21.85	30.12x11.93x21.85	30.12x11.93x21.85	30.12x11.93x21.85	31.69x12.99x21.81	35.04x13.46x26.50
Packing (WxDxH)	inch		34.84x14.76x23.81	34.84x14.76x23.81	34.84x14.76x23.81	34.84x14.76x23.81	34.84x14.76x23.81	37.0x16.14x23.81	40.55x17.24x28.74
Net/Gross Weight	lbs.		56.66/62.17	56.66/62.17	61.29/67.02	54.23/59.74	59.08/64.37	72.31/78.48	94.58/102.29
Refrigerant Type / Charge	oz.		R454B/21.52	R454B/21.52	R454B/24.34	R454B/21.52	R454B/24.69	R454B/40.57	R454B/53.62
Refrigerant Precharge Length	ft.		25	25	25	25	25	25	25
Additional Charge for Each ft.	oz/ft		0.16	0.16	0.16	0.16	0.16	0.16	0.32
Design Pressure	PSIG		550/340	550/340	550/340	550/340	550/340	550/340	550/340
Refrigerant Piping Liquid Side/Gas Side	inch		1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 1/2"	3/8" / 5/8"
Max. Pipe Length	ft.		82	82	82	82	82	98.4	164
Max. Difference in Level	ft.		49.2	49.2	49.2	49.2	49.2	65.6	82
Ambient Temperature	Cooling	°F	5-122	5-122	5-122	5-122	5-122	5-122	5-122
	Heating	°F	5-75	5-75	5-75	5-75	5-75	5-75	5-75
Certifications	ETL		✓	✓	✓	✓	✓	✓	✓
	AHRI		✓	✓	✓	✓	✓	✓	✓
	Energy Star for Cold Climate		✓	✓	✓	✓	✓	✓	✓
	NEEP		✓	✓	✓	✓	✓	✓	✓

# Ceiling Cassette



\*Panel sold separately, not included with Unit.

**UP TO 22.6 SEER2**  
9K, 12K, 18K, 24K, 36K, 48K Btu/h



Wall Thermostat should be connected to the unit to be Smart

## CONTROL OPTIONS

- Smart Kit Built In with Downloadable C&H app
- Remote Control Included
- 12V Wall Thermostat



Line Set Model 3/4"	Line Set Model 1/2"	Line Set Size
PJX-N1-C16FTW-MAX	PJX-N1-C16FTW-MAX-i05	1/4" - 3/8"
PJX-N1-C25FTW-MAX	PJX-N1-C25FTW-MAX-i05	1/4" - 3/8"
PJX-N1-C50FTW-MAX	PJX-N1-C50FTW-MAX-i05	1/4" - 3/8"
PJX-N2-C16FTW-MAX	PJX-N2-C16FTW-MAX-i05	1/4" - 1/2"
PJX-N2-C25FTW-MAX	PJX-N2-C25FTW-MAX-i05	1/4" - 1/2"
PJX-N2-C50FTW-MAX	PJX-N2-C50FTW-MAX-i05	1/4" - 1/2"
PJX-N3-C16FTW-MAX	PJX-N3-C16FTW-MAX-i05	3/8" - 5/8"
PJX-N3-C25FTW-MAX	PJX-N3-C25FTW-MAX-i05	3/8" - 5/8"
PJX-N3-C50FTW-MAX	PJX-N3-C50FTW-MAX-i05	3/8" - 5/8"
PJX-N4-C25FTW-MAX		3/8" - 3/4"
PJX-N4-C50FTW-MAX		3/8" - 3/4"
PJX-N6-C25FTW-MAX		3/8" - 7/8"
PJX-N6-C50FTW-MAX		3/8" - 7/8"



Refrigerant Sensor

Humidity Sensor

## INDOOR

			LIGHT COMMERCIAL						LIGHT COMMERCIAL					
Ceiling Cassette PRO (Model Numbers)			CH-RSH09-12MCT (Dip Switch for 9K)	CH-RSH09-12MCT (Dip Switch for 12K)	CH-RSH18MCT	CH-RSH24MCT	CH-RSH36LCCT	CH-RSH48LCCT	CH-RSH09-12MCT (Dip Switch 9)	CH-RSH09-12MCT (Dip Switch 12)	CH-RSH18MCT	CH-RSH24MCT	CH-RSH36LCCT	CH-RSH48LCCT
Ceiling Cassette (Model Numbers)			CH-RH09MCT	CH-RH12MCT	CH-RH18MCT	CH-RH24MCT	CH-RH36LCCT	CH-RH48LCCT	CH-RH09MCT	CH-RH12MCT	CH-RH18MCT	CH-RH24MCT	CH-RH36LCCT	CH-RH48LCCT
Panel Model Number			CH-NPNL09-18CT	CH-NPNL09-18CT	CH-NPNL09-18CT	CH-NPNL24-48CT	CH-NPNL24-48CT	CH-NPNL24-48CT	CH-NPNL09-18CT	CH-NPNL09-18CT	CH-NPNL09-18CT	CH-NPNL24-48CT	CH-NPNL24-48CT	CH-NPNL24-48CT
Power Supply	Rated	V, Ph, Hz	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60
Rated Capacity	Cooling	Btu/h	9,000	12,000	16,000	23,400	36,600	48,000	9,000	12,000	16,800	24,000	36,000	48,000
	Heating	Btu/h	10,000	12,000	19,000	25,000	37,000	53,000	10,000	12,000	18,000	25,000	38,000	50,000
Minimum Circuit Ampacity (MCA)	A		3	3	3	3	3	3	3	3	3	3	3	3
Max. Fuse	A		15	15	15	15	15	15	15	15	15	15	15	15
Indoor Air Flow (Turbo/Hi/Mi/Lo/Si)	CFM		417.9/364.9/306.1/194.2/147.2	417.9/364.9/306.1/194.2/147.2	447.3/388.5/317.8/194.2/147.2	765.2/706.3/635.7/547.4/N/A	1041.8/947.6/853.5/753.4/659.2	1236.1/1124.2/1018.3/800.5/688.7	417.9/364.9/306.1/194.2/147.2	417.9/364.9/306.1/194.2/147.2	447.3/388.5/317.8/194.2/147.2	765.2/706.3/635.7/547.4/N/A	1041.8/947.6/853.5/753.4/659.2	1236.1/1124.2/1018.3/800.5/688.7
Indoor Noise Level (Turbo/Hi/Mi/Lo/Si)	dB(A)		42.5/40/37.5/26/24	46/43.5/40.5/27.5/26	48/44.5/41/27.5/23.5	48.5/45/42.5/33.5/N/A	54/52.5/47/39.5/36.5	56/52.5/50/42.5/38.5	42.5/40/37.0/26.0/24.0	46/42.0/38.5/26.5/24.0	48/44.0/41.0/28.5/24.5	N/A/45.5/43.0/33.5/30.5	N/A/52.0/47.5/40.0/38.00	N/A/52.0/49.5/41.5/38.00
Indoor	Dimension (WxDxH)	inch	22.44x22.44x9.65	22.44x22.44x9.65	22.44x22.44x9.65	32.68x32.68x8.07	32.68x32.68x9.65	32.68x32.68x11.30	22.44x22.44x9.65	22.44x22.44x9.65	22.44x22.44x9.65	32.68x32.68x8.07	32.68x32.68x9.65	32.68x32.68x11.30
	Packing (WxDxH)	inch	28.15x25.20x11.61	28.15x25.20x11.61	28.15x25.20x11.61	35.83x35.83x9.84	35.83x35.83x11.42	35.83x35.83x12.99	28.15x25.20x11.61	28.15x25.20x11.61	28.15x25.20x11.61	35.83x35.83x9.84	35.83x35.83x11.42	35.83x35.83x12.99
	Net/Gross Weight	lbs.	35.27/41.89	35.27/41.89	35.27/41.89	47.18/59.08	59.30/71.43	64.59/76.06	35.27/41.89	35.27/41.89	35.27/41.89	47.18/59.08	59.30/71.43	64.59/76.06
Room Temperature	Cooling	°F	60-90	60-90	60-90	60-90	60-90	60-90	62-90	62-90	62-90	60-90	60-90	60-90
	Heating	°F	32-86	32-86	32-86	32-86	32-86	32-86	32-86	32-86	32-86	32-86	32-86	32-86
Liquid Side/Gas Side	inch		1/4"/3/8"	1/4"/3/8"	1/4"/1/2"	3/8"/5/8"	3/8"/3/4"	3/8"/3/4"	1/4"/3/8"	1/4"/3/8"	1/4"/1/2"	3/8"/5/8"	3/8"/3/4"	3/8"/3/4"

## OUTDOOR

			HYPER						REGULAR					
Outdoor Model			CH-RHP09-230VO	CH-RHP12-230VO	CH-RHP18-230VO	CH-RHP24-230VO	CH-RHP36LCU-230VO	CH-RHP48LCU-230VO	CH-RES09-230VO	CH-RES12-230VO	CH-RES18-230VO	CH-RES24-230VO	CH-R36LCU-230VO	CH-R48LCU-230VO
Power Supply	Rated	V, Ph, Hz	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60
	Voltage Range	V	187-253	187-253	187-253	187-253	187-253	187-253	187-253	187-253	187-253	187-253	187-253	187-253
Cooling	Rated Capacity Range	Btu/h	3,700-13,600	3,800-15,100	7,000-18,500	12,800-26,200	4,900-38,000	4,900-52,700	3,700-12,000	3,700-14,000	5,300-17,800	12,300-26,800	6,400-39,800	10,600-50,400
	Rated Current	A	4.8	4.6	8	8.9	13.5	21.0	4.5	4.3	6.1	8.8	16.4	22.5
	EER2		14	12.5	12.5	12	12	10	14.3	12.5	12.5	12	9.6	9.5
	SEER2		22.6	22.2	20	20.7	21.2	18	21.6	21.1	20.7	22	20	19
Heating at 47°F	Rated Capacity Range	Btu/h	5,100-15,700	5,300-16,200	8,700-20,000	11,500-30,700	11,400-44,600	19,000-57,400	4,700-13,700	4,700-15,000	7,100-21,500	11,600-33,100	14,400-42,200	19,900-61,700
	Rated current	A	3.3	4.4	11	9.5	14.1	22	3.3	4.3	7.2	10.2	15	22.1
	COP	W/W	4.00	3.70	3.18	3.54	3.43	3.09	4.00	3.55	3.36	3.20	3.31	2.96
	HSPF4		12.1	11.6	12.3	11.6	10.6	11.0	11.3	10.4	11.4	10.5	10.3	9.9
	HSPF5		9.3	8.9	9.5	9.2	7.9	7.7	8.8	7.9	8.5	8.1	8.8	8.8
Minimum Circuit Ampacity	A		15	15	19	24.9	38	44	12	12	18	24	33	39
Max.Fuse (Outdoor Unit)	A		15	15	20	25	40	45	15	15	20	25	35	40
Outdoor Air Flow (Max.)	CFM		1,471.5	1,471.5	1,765.8	2,236.7	3,001.9	4,237.9	1,236.1	1,236.1	1,765.8	2,236.7	2,413.3	4,237.9
Outdoor Noise Level (Sound Pressure)	dB(A)		55	57	57.5	61.5	64.5	62.5	54.5	54.5	57.5	59.5	63	62.5
Dimension (WxDxH)	inch		31.69x12.99x21.81	31.69x12.99x21.81	35.04x13.46x26.50	37.24x16.14x31.89	38.58x16.34x38.39	37.48x16.34x52.48	30.12x11.93x21.85	30.12x11.93x21.85	35.04x13.46x26.50	37.24x16.14x31.89	37.24x16.14x31.89	37.48x16.34x52.48
Packing (WxDxH)	inch		36.02x14.57x24.21	36.02x14.57x24.21	39.17x15.67x29.13	42.91x19.68x34.84	45.08x19.68x42.52	43.11x19.49x57.48	34.92x13.27x24.02	34.92x13.27x24.02	39.17x15.67x29.13	42.91x19.68x34.84	42.91x19.68x34.84	43.11x19.49x57.48
Net/Gross Weight	lbs.		72.75/78.70	72.75/78.70	99.87/107.80	130.29/141.31	206.57/237.44	208.78/239.86	62.17/67.68	62.17/67.68	92.59/100.31	122.13/132.28	152.34/162.48	208.78/239.86
Refrigerant Type / Charge	oz.		R454B/35.27	R454B/35.27	R454B/55.38	R454B/63.49	R454B/126.99	R454B/126.99	R454B/32.45	R454B/32.45	R454B/47.97	R454B/ 70.55	R454B/91.71	R454B/126.99
Refrigerant Precharge Length	ft.		25	25	25	25	25	25	25	25	25	25	25	25
Additional Charge for Each ft.	oz/ft		0.16	0.16	0.16	0.32	0.32	0.32	0.16	0.16	0.16	0.32	0.32	0.32
Design Pressure	PSIG		550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340
Refrigerant Piping Liquid Side/Gas Side	inch		1/4"/3/8"	1/4"/3/8"	1/4"/1/2"	3/8"/5/8"	3/8"/3/4"	3/8"/3/4"	1/4"/3/8"	1/4"/3/8"	1/4"/1/2"	3/8"/5/8"	3/8"/3/4"	3/8"/3/4"
Max. Pipe Length	ft.		82.00	82.00	98.40	164.00	246.00	246.00	82.00	82.00	98.40	164.00	246.00	246.00
Max. Difference in Level	ft.		49.20	49.20	65.60	82.00	98.40	98.40	49.20	49.20	65.60	82.00	98.40	98.40
Ambient Temperature	Cooling	°F	-22-122	-22-122	-22-122	-22-122	-22-122	-22-122	-13-122	-13-122	-13-122	-13-122	-13-122	-13-122
	Heating	°F	-22-75	-22-75	-22-75	-22-75	-22-75	-22-75	-13-75	-13-75	-13-75	-13-75	-13-75	-13-75
Certifications	ETL		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	AHRI		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Energy Star for Cold Climate		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	NEEP		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓



# One-Way Cassette



Wall Thermostat should be connected to the unit to be Smart



Refrigerant  
Sensor



Humidity  
Sensor

Line Set Model 3/4"	Line Set Model 1/2"	Line Set Size
PJX-N1-C16FTW-MAX	PJX-N1-C16FTW-MAX-i05	1/4" - 3/8"
PJX-N1-C25FTW-MAX	PJX-N1-C25FTW-MAX-i05	1/4" - 3/8"
PJX-N1-C50FTW-MAX	PJX-N1-C50FTW-MAX-i05	1/4" - 3/8"
PJX-N2-C16FTW-MAX	PJX-N2-C16FTW-MAX-i05	1/4" - 1/2"
PJX-N2-C25FTW-MAX	PJX-N2-C25FTW-MAX-i05	1/4" - 1/2"
PJX-N2-C50FTW-MAX	PJX-N2-C50FTW-MAX-i05	1/4" - 1/2"
PJX-N3-C16FTW-MAX	PJX-N3-C16FTW-MAX-i05	3/8" - 5/8"
PJX-N3-C25FTW-MAX	PJX-N3-C25FTW-MAX-i05	3/8" - 5/8"
PJX-N3-C50FTW-MAX	PJX-N3-C50FTW-MAX-i05	3/8" - 5/8"
PJX-N4-C25FTW-MAX		3/8" - 3/4"
PJX-N4-C50FTW-MAX		3/8" - 3/4"
PJX-N6-C25FTW-MAX		3/8" - 7/8"
PJX-N6-C50FTW-MAX		3/8" - 7/8"

*Designed for smaller spaces and fits perfectly between structural ceiling beams.*

INDOOR			CH-RSH06-12MCT1W (Dip Switch 6)	CH-RSH06-12MCT1W (Dip Switch 9)	CH-RSH06-12MCT1W (Dip Switch 12)	CH-RSH18MCT1W	CH-RSH06-12MCT1W (Dip Switch 9)	CH-RSH06-12MCT1W (Dip Switch 12)	CH-RSH18MCT1W
Power Supply	Rated	V, Ph, Hz	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60
Rated Capacity	Cooling	Btu/h	6,500	9,000	12,000	16,700	9,000	12,000	18,000
	Heating	Btu/h	7,400	10,900	12,500	20,000	11,000	12,000	18,000
Minimum Circuit Ampacity (MCA)		A	3	3	3	3	3	3	3
Max. Fuse		A	15	15	15	15	15	15	15
Indoor Air Flow (Turbo/Hi/Mi/Lo/Si)		CFM	353.2/312.0/282.5/ 247.2/176.6	353.2/312.0/282.5/ 247.2/176.6	353.2/312.0/282.5/ 247.2/176.6	400.2/352.0/300.2/ 207.2 / N/A	353.2/312/282.5/ 247.2/ N/A	353.2/312.0/282.5/ 247.2/176.6	400.2/352.0/300.2/ 207.2/ N/A
Indoor Noise Level (Hi/Mi/Lo)		dB(A)	37.5/35.5/26	38/36/33	41/37/33	44/41.5/31	38.5/34/24	43/37.5/26	44/41/29.5
Indoor	Dimension (WxDxH)	inch	50.31x13.19x8.98	50.31x13.19x8.98	50.31x13.19x8.98	50.31x13.19x8.98	50.31x13.19x8.98	50.31x13.19x8.98	50.31x13.19x8.98
	Packing (WxDxH)	inch	57.60x22.48x22.64	57.60x22.48x22.64	57.60x22.48x22.64	57.60x22.48x22.64	57.60x22.48x22.64	57.60x22.48x22.64	57.60x22.48x22.64
	Net/Gross Weight	lbs.	45.19/82.45	45.19/82.45	45.19/82.45	45.19/82.45	45.19/82.45	45.19/82.45	45.19/82.89
Room Temperature	Cooling	°F	60-90	60-90	60-90	60-90	60-90	60-90	60-90
	Heating	°F	32-86	32-86	32-86	32-86	32-86	32-86	32-86
Liquid Side/Gas Side		inch	1/4"/3/8"	1/4"/3/8"	1/4"/3/8"	1/4"/1/2"	1/4"/3/8"	1/4"/3/8"	1/4"/1/2"

OUTDOOR			HYPER				REGULAR		
Outdoor Model			CH-RHP06F9-230VO	CH-RHP09-230VO	CH-RHP12-230VO	CH-RHP18-230VO	CH-RES09-230VO	CH-RES12-230VO	CH-RES18-230VO
Power Supply	Rated	V, Ph, Hz	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60
	Voltage Range	V	187-253	187-253	187-253	187-253	187-253	187-253	187-253
Cooling	Rated Capacity (range)	Btu/h	3,600-11,200	4,000-12,900	4,000-13,900	5,700-19,000	3,700-11,400	3,900-13,800	4,000-18,800
	Rated Current	A	3	4.5	4.3	8.3	4.2	4.4	6.4
	EER2		15	14.6	13	12.5	14.4	12.3	12.5
	SEER2		22	24	23	20.6	22.1	22.1	22.2
Heating at 47°F	Rated Capacity Range	Btu/h	3,700-11,500	3,800-13,900	4,600-15,200	8,900-22,000	4,100-14,300	4,700-15,300	7,600-22,800
	Rated current	A	4.0	3.8	4.6	12	4.4	4.7	7.1
	COP	W/W	3.75	3.71	3.56	3.01	3.20	3.40	3.30
	HSPF4		12.0	12.1	10	12.2	11.8	10	12.2
	HSPF5		10.3	9.5	8	9.2	9.0	7.8	8.6
Minimum Circuit Ampacity		A	12	15	15	19	12	12	18
Max.Fuse (Outdoor Unit)		A	15	15	15	20	15	15	20
Outdoor Air Flow (Max.)		CFM	1236.1	1471.5	1471.5	1765.8	1236.1	1236.1	1765.8
Outdoor Noise Level (Sound Pressure)		dB(A)	53.5	54.5	56	59	54.5	54.5	57.5
Dimension (WxDxH)		inch	30.12x11.93x21.85	31.69x12.99x21.81	31.69x12.99x21.81	35.04x13.46x26.50	30.12x11.93x21.85	30.12x11.93x21.85	35.04x13.46x26.50
Packing (WxDxH)		inch	34.92x13.27x24.02	36.02x14.57x24.21	36.02x14.57x24.21	39.17x15.67x29.13	34.92x13.27x24.02	34.92x13.27x24.02	39.17x15.67x29.13
Net/Gross Weight		lbs.	62.17/67.68	72.75/78.70	72.75/78.70	99.87/107.80	62.17/67.68	62.17/67.68	92.59/100.31
Refrigerant Type / Charge		oz.	R454B/ 32.45	R454B/35.27	R454B/ 35.27	R454B/55.38	R454B/32.45	R454B/32.45	R454B/47.97
Refrigerant Precharge Length		ft.	25	25	25	25	25	25	25
Additional Charge for Each ft.		oz/ft	0.16	0.16	0.16	0.16	0.16	0.16	0.16
Design Pressure		PSIG	550/340	550/340	550/340	550/340	550/340	550/340	550/340
Refrigerant Piping Liq. Side / Gas Side		inch	1/4"/3/8"	1/4"/3/8"	1/4"/3/8"	1/4"/1/2"	1/4"/3/8"	1/4"/3/8"	1/4"/1/2"
Max. Pipe Length		ft.	82.02	82.02	82.02	98.42	82.00	82.00	98.40
Max. Difference in Level		ft.	49.21	49.21	49.21	65.62	49.20	49.20	65.60
Ambient Temperature	Cooling	°F	-22-122	-22-122	-22-122	-22-122	-13-122	-13-122	-13-122
	Heating	°F	-22-75	-22-75	-22-75	-22-75	-13-75	-13-75	-13-75
Certifications	ETL		✓	✓	✓	✓	✓	✓	✓
	AHRI		✓	✓	✓	✓	✓	✓	✓
	Energy Star for Cold Climate		✓	✓	✓	✓	✓	✓	✓
	NEEP		✓	✓	✓	✓	✓	✓	✓



## CONTROL OPTIONS

- Smart Kit Built In with Downloadable C&H app
- Remote Control Included
- 12V Wall Thermostat

Panel Dimensions (WxDxH) in 53.25 x 18.5 x 1

This panel dimension applies for all the indoor units (Panel Included).





# MINI FLOOR CONSOLE 9K, 12K AND 16K Btu/h REGULAR OR HYPER | SINGLE OR MULTI-ZONE



Refrigerant  
Sensor

Humidity  
Sensor



### CONTROL OPTIONS

- Smart Kit Built In with Downloadable C&H app
- Remote Control Included
- 12V Wall Thermostat



Wall Thermostat should be connected to the unit to be Smart

## FEATURES

- Compact Design
- Dual Air Outlets
- Refrigerant leakage detection sensor
- Humidity sensor
- Multiple Fan Speed Settings
- Smart Kit Built-In



			HYPER			REGULAR		
INDOOR	Indoor Model		CH-RSH09MMC	CH-RSH12MMC	CH-RSH16MMC	CH-RSH09MMC	CH-RSH12MMC	CH-RSH16MMC
	Power Supply	Rated	V, Ph, Hz	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60
Rated Capacity		Cooling	Btu/h	9,000	12,000	16,000	9,000	12,000
	Heating	Btu/h	9,000	12,000	17,000	9,000	12,000	17,000
Minimum Circuit Ampacity (MCA)		A	3	3	3	3	3	3
Max. Fuse		A	15	15	15	15	15	15
Indoor Air Flow (Turbo/Hi/Mi/Lo/Si)		CFM	441.4/376.7/323.7/188.4/129.5	441.4/376.7/323.7/188.4/129.5	500.3/441.4/382.6/323.7/206.0	441.4/376.7/323.7/188.4/129.5	441.4/376.7/323.7/188.4/129.5	500.3/441.4/382.6/323.7/206.0
Indoor Noise Level (Turbo/Hi/Mi/Lo/Si)		dB(A)	45/41.0/37.5/25.5/22	44/40.5/37.0/26.5/24	47/43.5/40.5/30.5/25.5	42/39.0/34.5/29.5/19.5	42/39/34.5/29.5/23.5	N/A/41.5/39.0/28.5/24.0
Indoor	Dimension (WxDxH)	inch	31.26x7.87x24.45	31.26x7.87x24.45	31.26x7.87x24.45	31.26x7.87x24.45	31.26x7.87x24.45	31.26x7.87x24.45
	Packing (WxDxH)	inch	34.06x11.02x28.31	34.06x11.02x28.31	34.06x11.02x28.31	34.06x11.02x28.31	34.06x11.02x28.31	34.06x11.02x28.31
	Net/Gross Weight	lbs.	32.85/41.89	32.85/41.89	32.85/41.89	32.85/41.89	32.85/41.89	32.85/41.89
Room Temperature	Cooling	°F	60-90	60-90	60-90	60-90	60-90	60-90
	Heating	°F	32-86	32-86	32-86	32-86	32-86	32-86
Liquid Side/Gas Side		inch	1/4"/3/8"	1/4"/1/2"	1/4"/1/2"	1/4"/3/8"	1/4"/3/8"	1/4"/1/2"

			HYPER			REGULAR		
OUTDOOR	Outdoor Model		CH-RHP09-230VO	CH-RHP12-230VO	CH-RHP18-230VO	CH-RES09-230VO	CH-RES12-230VO	CH-RES18-230VO
	Power Supply	Rated	V, Ph, Hz	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60
Voltage Range		V	187-253	187-253	187-253	187-253	187-253	187-253
Cooling	Rated Capacity Range	Btu/h	3,700-13,700	3,700-14,000	6,500-17,200	4,000-12,900	4,000-13,100	4,700-18,000
	Rated Current	A	4.2	4.3	8	4.2	4.2	5.8
	EER2		15.1	12.5	12.5	16.2	12.7	12.5
	SEER2		27.2	25.0	20	26	24.6	23.8
	HEATING AT 47°F	Rated Capacity Range	Btu/h	4,400-16,100	4,400-16,100	6,500-20,000	5,100-12,700	5,100-12,900
Heating at 47°F	Rated current	A	4.1	4	8	4.6	4	6.7
	COP	W/W	4.43	3.88	2.85	4.35	3.9	3.37
	HSPF4		10.9	10.5	10.3	13.9	11	13.5
Minimum Circuit Ampacity		A	15	15	19	12	12	18
	Max. Fuse (Outdoor Unit)	A	15	15	20	15	15	20
Outdoor	Dimension (WxDxH)	inch	31.69x12.99x21.81	31.69x12.99x21.81	35.04x13.46x26.50	30.12x11.93x21.85	30.12x11.93x21.85	35.04x13.46x26.50
	Packing (WxDxH)	inch	36.02x14.57x24.21	36.02x14.57x24.21	39.17x15.67x29.13	34.92x13.27x24.02	34.92x13.27x24.02	39.17x15.67x29.13
	Net/Gross Weight	lbs.	72.75/78.70	72.75/78.70	99.87/107.80	62.17/67.68	62.17/67.68	92.59/100.31
Refrigerant Type / Charge		oz.	R454B/35.27	R454B/35.27	R454B/55.38	R454B/32.45	R454B/32.45	R454B/47.97
Refrigerant Precharge Length		ft.	25	25	25	25	25	25
Additional Charge for Each ft.		oz/ft	0.16	0.16	0.16	0.16	0.16	0.16
Design Pressure		PSIG	550/340	550/340	550/340	550/340	550/340	550/340
Refrigerant Piping Liquid Side/Gas Side		inch	1/4"/3/8"	1/4"/1/2"	1/4"/1/2"	1/4"/3/8"	1/4"/3/8"	1/4"/1/2"
Max. Pipe Length		ft.	82	82	98.40	82	82	98.40
Max. Difference in Level		ft.	49.20	49.20	65.60	49.20	49.20	65.60
Ambient Temperature	Cooling	°F	-22-122	-22-122	-22-122	60-90	60-90	60-90
	Heating	°F	-22-75	-22-75	-22-75	32-86	32-86	32-86
Certifications	ETL		✓	✓	✓	✓	✓	✓
	AHRI		✓	✓	✓	✓	✓	✓
	Energy Star for Cold Climates		✓	✓	✓	✓	✓	✓
	NEEP		✓	✓	✓	✓	✓	✓

# Universal Floor Ceiling



Wall Thermostat should be connected to the unit to be Smart



18K, 24K, 36K, 48K, 60K Btu/h  
UP TO 22.3 SEER2



## CONTROL OPTIONS

- Smart Kit Built In with Downloadable C&H app
- Remote Control Included
- 12V Wall Thermostat



Refrigerant Sensor



Humidity Sensor



			HYPER					REGULAR				
			LIGHT COMMERCIAL					LIGHT COMMERCIAL				
INDOOR	Indoor Model		CH-RSH18MFC	CH-RSH24MFC	CH-RSH36LCFC	CH-RSH48LCFC	CH-RSH60LCFC	CH-RSH18MFC	CH-RSH24MFC	CH-RSH36LCFC	CH-RSH48LCFC	CH-RSH60LCFC
	Power Supply	Rated	V, Ph, Hz	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60
Rated Capacity	Cooling	Btu/h	17,000	22,000	36,400	48,000	54,000	18,000	24,000	36,000	48,000	54,000
	Heating	Btu/h	19,000	26,000	38,000	52,000	60,000	18,000	24,400	38,000	50,000	60,000
Minimum Circuit Ampacity (MCA)	A		1.9	2.5	3	3	3	1.9	2.5	3	3	3
Max. Fuse	A		15	15	15	15	15	15	15	15	15	15
Indoor Air Flow (Turbo/Hi/Mi/Lo/Si)	CFM		576.8/547.4/485.6/420.8/ N/A	735.8/706.3/606.3/453.2/376.7	1224.3/1088.9/988.8/ w765.2/653.3	1353.8/1236.1/1083.0/ 800.5/665.1	1365.6/1236.1/1118.3/ 882.9/777.0	576.8/547.4/485.6/420.8/ N/A	735.8/706.3/606.3/453.2/376.7	1224.3/1088.9/988.8/ 765.2/653.3	1353.8/1236.1/1083.0/ 800.5/665.1	1365.6/1236.1/1118.3/ 882.9/777.0
Indoor Noise Level (Turbo/Hi/Mi/Lo/Si)	dB(A)		45/42.5/39.5/30.5/29	51.5/49/45/34/29	N/A/51/45.5/39/35	54/53.0/48.5/39/35	N/A/54.5/49/42/39	N/A/43.0/40.0/32.0/29.0	51.5/49/45/34/29	50.5/49/44.5/37/33	N/A/53/49/39/34.5	N/A/54.5/49.5/41.5/38.5
Indoor	Dimension (WxDxH)	inch	42.05x26.57x9.25	42.05x26.57x9.25	64.96x26.57x9.25	64.96x26.57x9.25	64.96x26.57x9.25	42.05x26.57x9.25	42.05x26.57x9.25	64.96x26.57x9.25	64.96x26.57x9.25	64.96x26.57x9.25
	Packing (WxDxH)	inch	45.08x29.72x12.52	45.08x29.72x12.52	67.91x29.72x12.52	67.91x29.72x12.52	67.91x29.72x12.52	45.08x29.72x12.52	45.08x29.72x12.52	67.91x29.72x12.52	67.91x29.72x12.52	67.91x29.72x12.52
	Net/Gross Weight	lbs.	58.42/70.55	61.29/73.19	88.85/104.94	89.07/105.16	95.24/111.33	58.42/70.55	61.29/73.19	88.85/104.94	89.07/105.16	95.24/111.33
Room Temperature	Cooling	°F	60-90	60-90	60-90	60-90	60-90	60-90	60-90	60-90	60-90	60-90
	Heating	°F	32-86	32-86	32-86	32-86	32-86	32-86	32-86	32-86	32-86	32-86
Liquid Side/Gas Side	inch		1/4"/1/2"	3/8"/5/8"	3/8"/3/4"	3/8"/3/4"	3/8"/3/4"	1/4"/1/2"	3/8"/5/8"	3/8"/3/4"	3/8"/3/4"	3/8"/3/4"

			HYPER					REGULAR				
			LIGHT COMMERCIAL					LIGHT COMMERCIAL				
OUTDOOR	Outdoor Model		CH-RHP18-230VO	CH-RHP24-230VO	CH-RHP36LCU-230VO	CH-RHP48LCU-230VO	CH-RHP60LCU-230VO	CH-RES18-230VO	CH-RES24-230VO	CH-R36LCU-230VO	CH-R48LCU-230VO	CH-R60LCU-230VO
	Power Supply	Rated	V, Ph, Hz	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60
Voltage Range		V	187-253	187-253	187-253	187-253	187-253	187-253	187-253	187-253	187-253	187-253
Cooling	Rated Capacity Range	Btu/h	7,400-19,200	12,700-25,600	6,100-38,300	6,700-53,500	20,000-54,500	7,000-19,300	11,100-29,000	7,300-39,500	10,100-50,000	15,000-54,500
	Rated Current	A	8.7	8.2	13.3	22.5	26.2	6.4	8.6	15.3	22	24.6
	EER2		12.5	12	12	9.4	9	12.5	12.2	10.1	9.5	9.5
	SEER2		20.4	20.4	20	18.5	18	22.3	21.1	20	19.8	19.5
Heating at 47°F	Rated Capacity Range	Btu/h	8,300-20,700	11,300-29,500	11,100-45,400	18,800-58,700	21,700-65,500	7,200-22,200	11,800-32,600	14,100-40,400	15,800-59,100	20,200-60,000
	Rated current	A	11	10.1	15.1	24.2	26.1	7.2	10.4	14.3	22.6	26.2
	COP	W/W	3.07	3.34	3.29	2.86	3.02	3.30	2.99	3.34	2.82	3.05
	HSPF4		10.3	12.1	10.8	10.1	10.7	10.4	11.1	10	10.2	9.5
	HSPF5		8.2	9.8	8.9	8.0	8.5	8.0	8.4	7.7	7.8	7.2
Minimum Circuit Ampacity	A		19	24.9	38	44	44	18	24	33	39	42
Max.Fuse (Outdoor Unit)	A		20	25	40	45	45	20	25	35	40	45
Outdoor Air Flow (Max.)	CFM		1,765.8	2,236.7	3,001.9	4,237.9	4,237.9	1,765.8	2,236.7	2,413.3	4,237.9	4,237.9
Outdoor Noise Level (Sound Pressure)	dB(A)		58	61.5	65	64.5	64.5	57	59	64	62.5	63.5
Dimension (WxDxH)	inch		35.04x13.46x26.50	37.24x16.14x31.89	38.58x16.34x38.39	37.48x16.34x52.48	37.48x16.34x52.48	35.04x13.46x26.50	37.24x16.14x31.89	37.24x16.14x31.89	37.48x16.34x52.48	37.48x16.34x52.48
Packing (WxDxH)	inch		39.17x15.67x29.13	42.91x19.68x34.84	45.08x19.68x42.52	43.11x19.49x57.48	43.11x19.49x58.27	39.17x15.67x29.13	42.91x19.68x34.84	42.91x19.68x34.84	43.11x19.49x57.48	43.11x19.49x58.27
Net/Gross Weight	lbs.		99.87/107.80	130.29/141.31	206.57/237.44	208.78/239.86	230.38/261.69	42.0/45.5	55.4/60.0	152.34/162.48	208.78/239.86	209.44/240.08
Refrigerant Type / Charge	oz.		R454B/55.38	R454B/63.49	R454B/126.99	R454B/126.99	R454B/151.68	R454B/47.97	R454B/70.55	R454B/91.71	R454B/126.99	R454B/144.62
Refrigerant Precharge Length	ft.		25	25	25	25	25	25	25	25	25	25
Additional Charge for Each ft.	oz/ft		0.16	0.32	0.32	0.32	0.32	0.16	0.32	0.32	0.32	0.32
Design Pressure	PSIG		550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340
Refrigerant Piping Liquid Side/Gas Side	inch		1/4"/1/2"	3/8"/5/8"	3/8"/3/4"	3/8"/3/4"	3/8"/3/4"	1/4"/1/2"	3/8"/5/8"	3/8"/3/4"	3/8"/3/4"	3/8"/3/4"
Max. Pipe Length	ft.		98.42	164	246	246	246	98.40	164	246	246	246
Max. Difference in Level	ft.		65.60	82.00	98.40	98.40	98.40	65.60	82	98.40	98.40	98.40
Ambient Temperature	Cooling	°F	-22-122	-22-122	-22-122	-22-122	-22-122	-13-122	-13-122	-13-122	-13-122	-13-122
	Heating	°F	-22-75	-22-75	-22-75	-22-75	-22-75	-13-75	-13-75	-13-75	-13-75	-13-75
Certifications	ETL		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	AHRI		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Energy Star for Cold Climate		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	NEEP		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

			MEDIUM STATIC				HIGH STATIC			
			HYPER MULTIPLE CAPACITY (DIP SWITCH)			LIGHT COMMERCIAL				
Indoor Model			CH-RS06MDT-MS CH-RS06-12MDT-MS (Dip Switch 6K)	CH-RS09MDT-MS CH-RS06-12MDT-MS (Dip Switch 9K)	CH-RS12MDT-MS CH-RS06-12MDT-MS (Dip Switch 12K)	CH-RS18MDT-MS	CH-RS24MDT-MS	CH-RS36LCDT-MS	CH-RS48LCDT-MS	CH-RS60LCDT-MS
Power Supply	Rated	V, Ph, Hz	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60
Rated Capacity	Cooling	Btu/h	6,500	9,000	12,000	17,000	24,000	36,000	48,000	55,000
	Heating	Btu/h	8,000	10,000	12,500	19,000	26,000	42,000	52,000	60,000
Minimum Circuit Ampacity (MCA)		A	3	3	3	3	3	4	5	5
Max. Fuse		A	15	15	15	15	15	15	15	15
Indoor Air Flow (Turbo/Hi/Mi/Lo/Si)		CFM	323.7/264.9/206.0/147.2/117.7	323.7/264.9/206.0/147.2/117.7	400.2/323.7/264.9/176.6/117.7	600.4/559.2/500.3/441.4/N/A	853.5/706.3/618.0/500.3/N/A	1236.1/1059.5/941.8/765.2/N/A	1648.1/1471.5/1294.9/1059.5/N/A	2001.2/1706.9/1412.6/1118.3/N/A
Indoor Noise Level (Turbo/Hi/Mi/Lo/Si)		dB(A)	N/A/32.5/30.5/29.5/22	N/A/32.5/31/29.5/23	N/A/36/34.5/32.5/25.5	N/A/40/39/38/32	N/A/40/37/35/29.5	N/A/45/40/34/31	N/A/51/46/42/40	N/A/52/48/42/41
Indoor	Dimension (WxDxH)	inch	27.56 x 19.92 x 7.87	27.56 x 19.92 x 7.87	27.56 x 19.92 x 7.87	34.65 x 26.54 x 8.27	39.37 x 29.53 x 9.65	47.24 x 29.53 x 11.81	47.24 x 29.53 x 11.81	55.12 x 31.50 x 14.96
	Packing (WxDxH)	inch	33.86 x 21.26 x 11.22	33.86 x 21.26 x 11.22	33.86 x 21.26 x 11.22	42.13 x 28.54 x 11.02	48.23 x 33.86 x 11.97	56.10 x 33.86 x 14.13	56.10 x 33.86 x 14.13	62.99 x 36.02 x 17.52
	Net/Gross Weight	lbs.	39.46/46.74	39.46/46.74	39.46/46.74	54.45/66.14	80.47/91.93	106.26/120.37	111.33/124.78	161.38/178.13
Room Temperature	Cooling	°F	60-90	60-90	60-90	60-90	60-90	60-90	60-90	60-90
	Heating	°F	32-86	32-86	32-86	32-86	32-86	32-86	32-86	32-86
Liquid Side/Gas Side		inch	1/4"/3/8"	1/4"/3/8"	1/4"/3/8"	1/4"/1/2"	3/8"/5/8"	3/8"/3/4"	3/8"/3/4"	3/8"/3/4"

# Slim Duct Air Conditioners

6K-12K Multi-Capacity, 18K, 24K, 36K, 48K, 60K Btu/h



			HYPER							
Outdoor Model			CH-RHP06F9-230VO	CH-RHP09-230VO	CH-RHP12-230VO	CH-RHP18-230VO	CH-RHP24-230VO	CH-RHP36LCU-230VO	CH-RHP48LCU-230VO	CH-RHP60LCU-230VO
Power Supply	Rated	V, Ph, Hz	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60
	Voltage Range	V	187-253	187-253	187-253	187-253	187-253	187-253	187-253	187-253
Cooling	Rated Capacity Range	Btu/h	3,300-11,800	3,400-13,500	3,400-13,500	6,500-18,800	5,000-28,000	9,800-37,000	11,000-56,500	14,200-60,000
	Rated Current	A	3.4	4.8	4.6	9.1	8.8	13.5	19.9	23.5
	EER2		14.4	13.4	12.0	12.0	12.0	12.0	10.4	10.2
	SEER2		21.4	21.4	20.0	18.0	19.0	17.7	16.7	15.8
	Rated Capacity Range	Btu/h	3,700-13,100	3,800-16,200	3,800-16,200	8,900-22,000	7,300-31,400	11,000-45,500	11,200-60,000	11,200-66,000
Heating at 47°F	Rated current	A	4.5	3.9	5.0	10.5	8.8	14.1	19.0	20.9
	COP	W/W	4.01	3.53	3.39	3.37	3.81	3.80	3.60	3.74
	HSPF4		13.8	12.5	10	10.5	11.7	11.1	10.8	10.4
	HSPF5		10.8	9.7	8	9.0	9.3	9.2	8.8	8.7
Minimum Circuit Ampacity		A	12.0	15.0	15.0	19.0	24.9	38.0	44.0	44.0
Max. Fuse (Outdoor Unit)		A	15.0	15.0	15.0	20.0	25.0	40.0	45.0	45.0
Outdoor Air Flow (Max.)		CFM	1236.1	1471.5	1471.5	1,765.8	2,236.7	3,001.9	4,237.9	4,237.9
Outdoor Noise Level (Sound Pressure)		dB(A)	54.0	56.0	56.0	59.0	61.0	65.0	65.0	63.0
Outdoor	Dimension (WxDxH)	inch	30.12 x 11.93 x 21.85	31.69 x 12.99 x 21.81	31.69 x 12.99 x 21.81	35.04 x 13.46 x 26.50	37.24 x 16.14 x 31.89	38.58 x 16.34 x 38.39	37.48 x 16.34 x 52.48	37.48 x 16.34 x 52.48
	Packing (WxDxH)	inch	34.92 x 13.27 x 24.02	36.02 x 14.57 x 24.21	36.02 x 14.57 x 24.21	39.17 x 15.67 x 29.13	42.91 x 19.68 x 34.84	45.08 x 19.68 x 42.52	43.11 x 19.49 x 57.48	43.11 x 19.49 x 58.27
	Net/Gross Weight	lbs.	62.17/67.68	72.75/78.70	72.75/78.70	99.87/107.80	130.29/141.31	206.57/237.44	208.78/239.86	230.38/261.69
Refrigerant Type / Charge		oz.	R454B / 32.45	R454B / 35.27	R454B / 35.27	R454B / 55.38	R454B / 63.49	R454B / 126.99	R454B / 126.99	R454B / 151.68
Refrigerant Precharge Length		ft.	25	25	25	25	25	25	25	25
Additional Charge for Each ft.		oz/ft	0.16	0.16	0.16	0.16	0.32	0.32	0.32	0.32
Design Pressure		PSIG	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340
Refrigerant Piping Liquid Side/Gas Side		inch	1/4"/3/8"	1/4"/3/8"	1/4"/3/8"	1/4"/1/2"	3/8"/5/8"	3/8"/3/4"	3/8"/3/4"	3/8"/3/4"
Max. Pipe Length		ft.	82.0	82.0	82.0	98.40	164.0	246.0	246.0	246.0
Max. Difference in Level		ft.	32.8	32.8	32.8	65.60	82.00	98.40	98.40	98.40
Ambient Temperature	Cooling	°F	-22-122	-22-122	-22-122	-22-122	-22-122	-22-122	-22-122	-22-122
	Heating	°F	-22-75	-22-75	-22-75	-22-75	-22-75	-22-75	-22-75	-22-75
Certifications	ETL		✓	✓	✓	✓	✓	✓	✓	✓
	AHRI		✓	✓	✓	✓	✓	✓	✓	✓
	Energy Star for Cold Climates		✓	✓	✓	✓	✓	✓	✓	✓
	NEEP		✓	✓	✓	✓	✓	✓	✓	✓



Refrigerant  
Sensor

Wall Thermostat should be connected to the unit to be Smart



**CONTROL OPTIONS**  
• Remote Control Included  
• 12V Wall Thermostat

Line Set Model 3/4"	Line Set Model 1/2"	Line Set Size
PJX-N1-C16FTW-MAX	PJX-N1-C16FTW-MAX-i05	1/4" - 3/8"
PJX-N1-C25FTW-MAX	PJX-N1-C25FTW-MAX-i05	1/4" - 3/8"
PJX-N1-C50FTW-MAX	PJX-N1-C50FTW-MAX-i05	1/4" - 3/8"
PJX-N2-C16FTW-MAX	PJX-N2-C16FTW-MAX-i05	1/4" - 1/2"
PJX-N2-C25FTW-MAX	PJX-N2-C25FTW-MAX-i05	1/4" - 1/2"
PJX-N2-C50FTW-MAX	PJX-N2-C50FTW-MAX-i05	1/4" - 1/2"
PJX-N3-C16FTW-MAX	PJX-N3-C16FTW-MAX-i05	3/8" - 5/8"
PJX-N3-C25FTW-MAX	PJX-N3-C25FTW-MAX-i05	3/8" - 5/8"
PJX-N3-C50FTW-MAX	PJX-N3-C50FTW-MAX-i05	3/8" - 5/8"
PJX-N4-C25FTW-MAX		3/8" - 3/4"
PJX-N4-C50FTW-MAX		3/8" - 3/4"
PJX-N6-C25FTW-MAX		3/8" - 7/8"
PJX-N6-C50FTW-MAX		3/8" - 7/8"

# Slim Duct Air Conditioners


6K-12K Multi-Capacity, 18K, 24K, 36K, 48K, 60K Btu/h

**DIP SWITCH:** ENC1 dip switch is used for capacity change.


When matching with single zone condensers, the indoor unit will automatically adjust to 6,000 BTU/H, 9,000 BTU/H or 12,000 BTU/H according to condensers capacity.

When matching with multi-zone condensers, it needs to set the ENC1. Change the capacity of indoor unit to 6,000 BTU/H by adjusting the dip switch ENC1 from "0" to "1". Change the capacity of indoor unit to 9,000 BTU/H by adjusting the dip switch ENC1 from "0" to "2". Change the capacity of indoor unit to 12,000 BTU/H by adjusting the dip switch ENC1 from "0" to "3".


Dip switch change for 6,000BTU/H



Dip switch change for 9,000BTU/H



Dip switch change for 12,000BTU/H



			MEDIUM STATIC			HIGH STATIC				
			MULTIPLE CAPACITY (DIP SWITCH)			LIGHT COMMERCIAL				
			REGULAR							
INDOOR	Indoor Model		CH-RS09MDT-MS CH-RS06-12MDT-MS (Dip Switch 9K)	CH-RS12MDT-MS CH-RS06-12MDT-MS (Dip Switch 12K)	CH-RS18MDT-MS	CH-RS24MDT-MS	CH-RS36LCDT-MS	CH-RS48LCDT-MS	CH-RS60LCDT-MS	
	Power Supply	Rated	V, Ph, Hz	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60	
	Rated Capacity	Cooling	Btu/h	9,000	11,500	17,000	24,000	36,000	48,000	58,000
		Heating	Btu/h	10,000	12,000	20,000	25,000	40,000	50,000	60,000
	Minimum Circuit Ampacity (MCA)		A	3	3	3	3	4	5	5
	Max. Fuse		A	15	15	15	15	15	15	15
	Indoor Air Flow (Turbo/Hi/Mi/Lo/Si)		CFM	400.2/323.7/264.9/176.6/117.7	400.2/323.7/264.9/176.6/117.7	600.4/559.2/500.3/441.4/N/A	853.5/706.3/618.0/500.3/N/A	1236.1/1059.5/941.8/765.2/N/A	1648.1/1471.5/1294.9/1059.5/N/A	2001.2/1706.9/1412.6/1118.3/N/A
	Indoor Noise Level (Turbo/Hi/Mi/Lo/Si)		dB(A)	N/A/34/32.5/29/24	N/A/37/35/33.5/26	N/A/40.5/39/38/35	43/40/38/35.5/29.5	N/A/45/39.5/33/30	N/A/51/46/42/40	N/A/52/48/43/42
	Indoor	Dimension (WxDxH)	inch	27.56 x 19.92 x 7.87	27.56 x 19.92 x 7.87	34.65 x 26.54 x 8.27	39.37 x 29.53 x 9.65	47.24 x 29.53 x 11.81	47.24 x 29.53 x 11.81	55.12 x 31.50 x 14.96
		Packing (WxDxH)	inch	33.86 x 21.26 x 11.22	33.86 x 21.26 x 11.22	42.13 x 28.54 x 11.02	48.23 x 33.86 x 11.97	56.10 x 33.86 x 14.13	56.10 x 33.86 x 14.13	62.99 x 36.02 x 17.52
Net/Gross Weight		lbs.	39.46/46.74	39.46/46.74	54.45/66.14	80.47/91.93	106.26/120.37	111.33/124.78	161.38/178.13	
Room Temperature	Cooling	°F	60-90	60-90	60-90	60-90	60-90	60-90	60-90	
	Heating	°F	32-86	32-86	32-86	32-86	32-86	32-86	32-86	
Liquid Side/Gas Side		inch	1/4"/3/8"	1/4"/3/8"	1/4"/1/2"	3/8"/5/8"	3/8"/3/4"	3/8"/3/4"	3/8"/3/4"	

			REGULAR							
OUTDOOR	Outdoor Model			CH-RES09-230VO	CH-RES12-230VO	CH-RES18-230VO	CH-RES24-230VO	CH-R36LCU-230VO	CH-R48LCU-230VO	CH-R60LCU-230VO
	Power Supply	Rated	V, Ph, Hz	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60	208/230,1, 60
		Voltage Range	V	187-253	187-253	187-253	187-253	187-253	187-253	187-253
	Cooling	Rated Capacity Range	Btu/h	3,100-11,900	3,100-13,000	7,000-19,000	8,500-28,300	7,900-42,500	11,000-56,500	14,600-63,000
		Rated Current	A	4.7	4.5	6.2	8.3	15.3	21.3	25.6
		EER2		12.8	11.7	12.5	12.5	10.1	10.0	10.0
		SEER2		19.5	19.0	20.0	19	18.7	17.1	17.0
	Heating at 47°F	Rated Capacity Range	Btu/h	3,600-14,000	3,700-15,600	5,500-22,000	11,800-35,100	8,100-43,500	11,200-60,500	11,800-67,000
		Rated current	A	3.6	4.7	7.2	8.7	14.2	19.0	21.0
		COP	W/W	3.66	3.42	3.47	3.64	3.70	3.49	3.70
HSPF4			11.0	10.2	10.5	11.0	10.2	9.8	9.7	
		HSPF5		8.8	8.0	8.2	8.5	7.8	7.7	7.6
Minimum Circuit Ampacity		A	12.0	12.0	18.0	24.0	33.0	39.0	42.0	
Max.Fuse (Outdoor Unit)		A	15.0	15.0	20.0	25.0	35	40	45	
Outdoor Air Flow (Max.)		CFM	1236.1	1236.1	1765.8	2236.7	2413.3	4237.9	4237.9	
Outdoor Noise Level (Sound Pressure)		dB(A)	54.0	55.5	59.0	60.0	63.0	64.0	64.0	
Outdoor	Dimension (WxDxH)	inch	30.12 x 11.93 x 21.85	30.12 x 11.93 x 21.85	35.04 x 13.46 x 26.50	37.24 x 16.14 x 31.89	37.24 x 16.14 x 31.89	37.48 x 16.34 x 52.48	37.48 x 16.34 x 52.48	
	Packing (WxDxH)	inch	34.92 x 13.27 x 24.02	34.92 x 13.27 x 24.02	39.17 x 15.67 x 29.13	42.91 x 19.68 x 34.84	42.91 x 19.68 x 34.84	43.11 x 19.49 x 57.48	43.11 x 19.49 x 58.27	
	Net/Gross Weight	lbs.	62.17/67.68	62.17/67.68	92.59/100.31	122.13/132.28	152.34/162.48	208.78/239.86	209.44/240.08	
Refrigerant Type / Charge		oz.	R454B / 32.45	R454B / 32.45	R454B / 47.97	R454B / 70.55	R454B / 91.71	R454B / 126.99	R454B / 144.62	
Refrigerant Precharge Length		ft.	25	25	25	25	25	25	25	
Additional Charge for Each ft.		oz/ft	0.16	0.16	0.16	0.32	0.32	0.32	0.32	
Design Pressure		PSIG	550/340	550/340	550/340	550/340	550/340	550/340	550/340	
Refrigerant Piping Liquid Side/Gas Side		inch	1/4"/3/8"	1/4"/3/8"	1/4"/1/2"	3/8"/5/8"	3/8"/3/4"	3/8"/3/4"	3/8"/3/4"	
Max. Pipe Length		ft.	82.0	82.0	98.40	164.0	246.00	246.00	246.00	
Max. Difference in Level		ft.	49.2	49.2	65.6	82.0	98.4	98.4	98.4	
Ambient Temperature	Cooling	°F	-13-122	-13-122	-13-122	-13-122	-13-122	-13-122	-13-122	
	Heating	°F	-13-75	-13-75	-13-75	-13-75	-13-75	-13-75	-13-75	
Certifications	ETL		✓	✓	✓	✓	✓	✓	✓	
	AHRI		✓	✓	✓	✓	✓	✓	✓	
	Energy Star for Cold Climate		✓	✓	✓	✓	✓	✓	✓	
	NEEP		✓	✓	✓	✓	✓	✓	✓	

# MULTI-POSITION AIR HANDLER UNIT

## AHU 18K, 24K, 30K, 36K, 48K, 60K Btu/h



Wall Thermostat should be connected to the unit to be Smart



Refrigerant Sensor

- INTELLIGENT AIR FLOW
- ANTI-COLD AIR FUNCTION
- TU1 COPPER TUBES
- FAST COOL/HEAT FUNCTION
- ALUMINUM COIL
- AUXILIARY HEATER
- AUTO RESTART FUNCTION
- REFRIGERANT LEAK DETECTION
- WIRED CONTROLLER
- TRUE MULTI-POSITION AIR HANDLER

AHU Capacity	5KW heater	10KW heater	15KW heater	20KW heater
	One group	One group	Two groups	Two groups
	10KW+5KW	10KW+5KW	10KW+5KW	10KW+10KW
	W1 on 5KW	W1 on 10KW	W1 on 10KW	W1 on 10KW
Model	CH-NREH05KW	CH-NREH10KW	CH-NREH15KW	CH-NREH20KW
18K(AHU)	Y	Y	-	-
24K(AHU)	Y	Y	Y	-
30K(AHU)	Y	Y	Y	Y
36K(AHU)	Y	Y	Y	Y
48K(AHU)	-	Y	Y	Y
60K(AHU)	-	Y	Y	Y

Electric Heater	Power	1.5 ton (18,000 BTU/h)	2 ton (24,000 BTU/h)	3 ton (30,000 BTU/h)	4 ton (36,000 BTU/h)	5 ton (48,000 BTU/h)	6 ton (60,000 BTU/h)
	Model	CH-RS18MAHU	CH-RS24MAHU	CH-RS30MAHU	CH-RS36LCAHU	CH-RS48LCAHU	CH-RS60LCAHU
5KW	Y	Y	Y	Y	Y	-	-
10KW	Y	Y	Y	Y	Y	Y	Y
15KW	-	Y	Y	Y	Y	Y	Y
20KW	-	-	Y	Y	Y	Y	Y

### CONTROL OPTIONS

- 12V Wall Thermostat
- Remote control Included
- Downloadable C&H app



INDOOR			CH-RS18MAHU	CH-RS24MAHU	CH-RS36LCAHU	CH-RS48LCAHU	CH-RS60LCAHU	CH-RS18MAHU	CH-RS24MAHU	CH-RS30MAHU	CH-RS36LCAHU	CH-RS48LCAHU	CH-RS60LCAHU
Power Supply	Rated	V, Ph, Hz	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60
	Voltage range	V	187-253	187-253	187-253	187-253	187-253	187-253	187-253	187-253	187-253	187-253	187-253
Cooling	Rated Capacity	Btu/h	18,000	23,000	36,000	48,000	54,000	18,000	24,000	30,000	36,000	48,000	60,000
	Rated Current	A	9.1	8.7	13.4	22	24	6.7	9.3	12.5	17.4	21.5	25.5
Heating	Rated Capacity	Btu/h	19,500	26,000	38,000	50,000	59,000	18,000	25,000	30,000	38,000	50,000	59,000
	Rated Current	A	9.5	9.7	14.3	19	21.8	6.7	9.2	11.2	14.4	22	24
Minimum Circuit Ampacity (MCA)	A		3.5	4	5	7.5	9	3.5	4	6	6	9.8	11
Max. Fuse	A		15	15	15	15	15	15	15	15	15	15	15
Indoor Air Flow (Turbo/Hi/Mi/Lo/Si)	CFM		618.0/576.8/529.7/488.5 / N/A	824.0/759.3/694.5/629.8 / -	1189/1083/971.2/865.2 / N/A	1601/1471.5/1283.1/1094.8 / /	1807/1553.9/1353.8/724 / N/A	618.0/576.8/529.7/488.5 / N/A	824.0/759.3/694.5/629.8 / N/A	988.8/894.7/806.4/712.2 / N/A	1189.0/1083.0/971.2/865.2 / N/A	1601.0/1471.5/1283.1/1094.8 / N/A	1807.0/1553.9/1353.8/724.0 / N/A
Indoor Noise Level (Turbo/Hi/Mi/Lo/Si)	dB(A)		N/A/42.5/37.5/30.0/N/A	N/A/43.5/40.0/25.5/N/A	N/A/47/42/30.5/N/A	56.5/54.5/51/48//	N/A/53.0/48.0/33.5/N/A	N/A/42/39.5/33/N/A	N/A/43.5/41.5/28.5/N/A	N/A/44/41/26/N/A	N/A/47.0/42.0/31.0/N/A	56.5/54.5/51/48/N/A	N/A/51/48/42.5/N/A
ESP	Range		0-0.8	0-0.8	0-0.8	0-0.8	0-0.8	0-0.8	0-0.8	0-0.8	0-0.8	0-0.8	0-0.8
Indoor	Dimension (WxDxH)	inch	17.52x21.02x45	17.52x21.02x 5	21.02x21.02x49.02	24.49x21.02x52.99	24.49x21.02x52.99	17.52x21.02x45	17.52x21.02x45	21.02x21.02x49.02	21.02x21.02x49.02	24.49x21.02x52.99	24.49x21.02x52.99
	Packing (WxDxH)	inch	20.87x26.57x48.62	20.87x26.57x48.62	24.41x26.57x52.56	27.95x26.77x56.50	27.95x26.77x56.50	20.87x26.57x48.62	20.87x26.57x48.62	24.41x26.57x52.56	24.41x26.57x52.56	27.95x26.77x56.50	27.95x26.77x56.50
	Net/Gross Weight	lbs.	104.72/125.66	104.28/125.88	127.87/152.78	161.82/191.58	164.02/189.82	104.72/125.66	104.28/125.88	127.43/151.68	127.87/152.78	161.82/191.58	164.02/189.82
Room Temperature	Cooling	°F	60-90	60-90	60-90	60-90	60-90	60-90	60-90	60-90	60-90	60-90	60-90
	Heating	°F	32-86	32-86	32-86	32-86	32-86	32-86	32-86	32-86	32-86	32-86	32-86
Liquid Side/Gas side	inch		1/4" / 1/2"	3/8" / 5/8"	3/8" / 3/4"	3/8" / 3/4"	3/8" / 3/4"	1/4" / 1/2"	3/8" / 5/8"	3/8" / 5/8"	3/8" / 3/4"	3/8" / 3/4"	3/8" / 3/4"

### HYPER

### REGULAR

OUTDOOR			CH-RHP18-230V0	CH-RHP24-230V0	CH-RHP36LCU-230V0	CH-RHP48LCU-230V0	CH-RHP60LCU-230V0	CH-RES18-230V0	CH-RES24-230V0	CH-REL30-230V0	CH-R36LCU-230V0	CH-R48LCU-230V0	CH-R60LCU-230V0	
Power Supply	Rated	V, Ph, Hz	208-230, 1, 60	208-230, 1, 60	208-230, 1, 60	208-230, 1, 60	208-230, 1, 60	208-230, 1, 60	208-230, 1, 60	208-230, 1, 60	208-230, 1, 60	208-230, 1, 60	208-230, 1, 60	
	Voltage range	V	187-253	187-253	187-253	187-253	187-253	187-253	187-253	187-253	187-253	187-253	187-253	
Cooling	Rated Current	A	9.1	8.7	13.4	22	24	6.7	9.3	12.5	17.4	21.5	25.5	
	Rated Capacity Range	Btu/h	6,000-20,400	7,500-27,000	5,700-36,400	7,300-55,500	13,700-58,000	5,600-20,400	6,700-29,600	9,200-34,000	8,900-38,200	9,500-52,000	21,800-57,300	
Heating at 47°F	EER2		12	12	11.7	10	10	12.1	11.7	11	9	10	9.5	
	SEER2		18	18.7	17.2	17	15.2	18.5	19.7	17	15.8	17.7	16	
	Rated Capacity Range	Btu/h	5,000-21,600	8,800-29,000	9,500-44,000	9,500-65,000	10,000-66,100	5,500-21,800	5,800-33,800	8,500-33,000	6,400-43,000	11,700-60,000	11,800-60,300	
	COP	W/W	3.64	3.5	3.39	3.5	3.36	3.60	3.53	3.60	3.36	3.5	3.44	
Heating at 5°F (-15°C)	HSPF4		10	10	9.5	10.2	9.2	9.8	9	8.7	9.3	10	9.1	
	HSPF5		8.3	8	8	8.1	7.7	7.7	7.3	7	7.3	7.7	7.2	
Rated Capacity	Btu/h		18,000	23,600	38,000	46,000	53,000	13,000	18,000	20,400	24,200	35,200	35,400	
Minimum Circuit Ampacity (MCA)	A		19	24.9	38	44	44	18	24	28	33	39	42	
Max. Fuse	A		20	25	40	45	45	20	25	30	35	40	45	
Outdoor Air Flow (Max.)	CFM		1,765.8	2,236.7	3,001.9	4,237.9	4,237.9	1,765.8	2,236.7	2,236.7	2,413.3	4,237.9	4,237.9	
Outdoor Noise Level	dB(A)		59	61.5	65.5	65	62	56.5	58.5	61	62.5	65	62.5	
Outdoor Unit	Dimension (WxDxH)	inch	35.04x13.46x26.50	37.24x16.14x31.89	38.58x16.34x38.39	37.48x16.34x52.48	37.48x16.34x52.48	35.04x13.46x26.50	37.24x16.14x31.89	37.24x16.14x31.89	37.24x16.14x31.89	37.24x16.14x31.89	37.48x16.34x52.48	37.48x16.34x52.48
	Packing (WxDxH)	inch	39.17x15.67x29.13	42.91x19.68x34.84	45.08x19.68x42.52	43.11x19.49x57.48	43.11x19.49x58.27	39.17x15.67x29.13	42.91x19.68x34.84	42.91x19.68x34.84	42.91x19.68x34.84	42.91x19.68x34.84	43.11x19.49x57.48	43.11x19.49x58.27
	Net/Gross Weight	lbs.	99.87/107.80	130.29/141.31	206.57/237.44	208.78/239.86	230.38/261.69	92.59/100.31	122.13/132.28	142.86/154.54	152.34/162.48	208.78/239.86	209.44/240.08	
Refrigerant Type/Quantity	oz.		R454B/55.38	R454B/63.49	R445B/126.99	R445B/126.99	R445B/151.68	R454B/47.97	R454B/70.55	R454B/84.66	R454B/91.71	R454B/126.99	R454B/144.62	
Refrigerant Precharge	ft.		25	25	25	25	25	25	25	25	25	25	25	
Additional Charge for each ft.	oz./ft.		0.16	0.32	0.32	0.32	0.32	0.16	0.32	0.32	0.32	0.32	0.32	
Design Pressure	PSIG		550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340	
Refrigerant piping Liquid side/Gas Side	inch		1/4" / 1/2"	3/8" / 5/8"	3/8" / 3/4"	3/8" / 3/4"	3/8" / 3/4"	1/4" / 1/2"	3/8" / 5/8"	3/8" / 5/8"	3/8" / 3/4"	3/8" / 3/4"	3/8" / 3/4"	
Max. Pipe Length	ft.		98.4	164	246	246	246	98.4	164	164	246	246	213.2	
Max. Difference in Level	ft.		65.6	82	98.4	98.4	98.4	65.6	82	82	98.4	98.4	98.4	
Ambient Temperature	Cooling	ft.	-22-122	-22-122	5-122	5-122	5-122	-13-122	-13-122	-13-122	-13-122	-13-122	-13-122	
	Heating	°F	-22-75	-22-75	-22-75	-22-75	-22-75	-13-75	-13-75	-13-75	-13-75	-13-75	-13-75	
Certifications	AHRI		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	ETL		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	Energy Star for Cold Climate		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	NEEP		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	



# PEAQ

# PEAQ

SEER2: Up to 19  
EER2: Up to 12.5  
HSPF2: Up to 10.8  
COP: Up to 3.6  
STATIC PRESSURE: Up to 1.2"

SAME WIDTH AS YOUR EXISTING GAS FURNACE



18K TO 55K BTU  
SINGLE-ZONE

Full range of options to fit your lifestyle needs.

ADAPTIVE VOLTAGE  
115V TO 208/230V

Automatically identifying the required voltage, no need for manual conversion.

M-COIL  
SYMMETRIC FAN BLOWER

Optimized structure brings even airflow and higher efficiency heat exchange.

100% HEATING  
OUTPUT AT 0°F

Extraordinary Cold Climate Heating Performance



Refrigerant Sensor



WATCH OUR  
INFORMATIONAL  
VIDEO

**COOPER&HUNTER** MAKES IT EASY TO REPLACE YOUR EXISTING GAS FURNACE SYSTEMS

# PEAQ

## MULTI-VOLTAGE AIR HANDLER UNIT

AHU 18K, 24K, 33K, 36K, 48K, 55K Btu/h

**ADAPTIVE MULTI-VOLTAGE - 115V & 208-230V:** All in one 115/208-230V Automatically identifying the required voltage without the need for manual conversion, eliminating the hassle of rewiring.

**M-COIL:** 2% Airflow difference between evaporators less than 0.02 in. W.C. pressure drop.

**TU1 COPPER TUBES:** Oxygen-free copper with higher purity copper content of over 99.97%, providing excellent electrical and thermal conductivity and superior corrosion and cold resistance.

**SYMMETRIC FAN BLOWER DESIGN:** Optimized structure brings even airflow and higher efficiency heat exchange.

**SLIMMER INDOOR UNITS:** The same width as most gas furnaces 14.5"-21.5" making the PEAQ unit an ideal replacement for your gas furnace.

**AUXILIARY HEATER:** Purchased separately as a backup heat option for indoor units, available in 5kW, 10kW, 15kW, and 20kW models.

**REFRIGERANT LEAK SENSORS:** Protects the compressor from damage due to refrigerant leaks by alerting user with error code "EC".

**WIRED THERMOSTAT CONTROLLER INCLUDED:** Also compatible with most third party 24V wired thermostats.

**SMART KIT BUILT-IN:** C&H's Smart Kit enables control from anywhere with C&H Remote app using any IOS or Android smart device.

**TRUE MULTI-POSITION AIR HANDLER:** Unit can be installed in Horizontal or Vertical, upward or downward positions for optimal space usage.




### CONTROL OPTIONS

- 12V Wall Thermostat
- Remote control included
- Downloadable C&H app



Wall Thermostat should be connected to the unit to be Smart



AHU Capacity	5kW heater	10kW heater	15kW heater	20kW heater
	One group	One group	Two groups	Two groups
	10KW+5KW	10KW+5KW	10KW+5KW	10KW+10KW
Model	CH-PQEH05KW	CH-PQEH10KW	CH-PQEH15KW	CH-PQEH20KW
18K(AHU)	Y	Y	-	-
24K(AHU)	Y	Y	Y	-
33K(AHU)	Y	Y	Y	Y
36K(AHU)	Y	Y	Y	Y
48K(AHU)	-	Y	Y	Y
55K(AHU)	-	Y	Y	Y

Electric Heater	Power (BTU/h)	1.5 ton (18,000)	2 ton (24,000)	3 ton (30,000)	4 ton (36,000)	5 ton (48,000)	5 ton (54,000)
	Model	CH-PQ18AHU	CH-PQ24AHU	CH-PQ33AHU	CH-PQ36AHU	CH-PQ48AHU	CH-PQ55AHU
5KW	Y	Y	Y	Y	-	-	-
10KW	Y	Y	Y	Y	Y	Y	Y
15KW	-	Y	Y	Y	Y	Y	Y
20KW	-	-	Y	Y	Y	Y	Y

### HIGH PERFORMANCE HYPER

INDOOR			CH-PQ18AHU	CH-PQ24AHU	CH-PQ33AHU	CH-PQ36AHU	CH-PQ48AHU	CH-PQ55AHU
Indoor Model								
Power Supply	Rated	V, Ph, Hz	115/208/230, 1, 60	115/208/230, 1, 60	115/208/230, 1, 60	115/208/230, 1, 60	115/208/230, 1, 60	115/208/230, 1, 60
	Rated Capacity	Btu/h	18,000	24,000	30,000	36,000	48,000	54,000
Cooling	Rated Current	A	9.3	9.1	11.4	13.4	18	20.5
	Rated Capacity	Btu/h	18,000	24,000	33,000	36,000	48,000	54,000
Heating	Rated Capacity	Btu/h	18,000	24,000	33,000	36,000	48,000	54,000
	Rated Current	A	9.4	9.1	12.3	13.3	18.9	21.5
Minimum Circuit Ampacity (MCA)	A		5.5/3.5	5.5/3.5	8.0/6.05	8.0/6.0	14.5/10	14.5/10
Max. Fuse	A		15	15	15	15	15	15
Indoor Air Flow (TurboHi/Mi/Lo)	CFM		618.0/576.8/529.7/488.5	824.0/759.3/694.5/629.8	988.8/894.7/806.4/712.2	1236.1/1147.8/1059.5/971.2	1601.0/1442.1/1265.5/1088.9	1801.1/1648.1/1500.9/1236.1
Indoor Noise Level (TurboHi/Mi/Lo)	dB(A)		N/A/42.5/40.5/37	N/A/47.5/44/33	49/47/45.5/31.5	N/A/49.5/48/31.5	N/A/53.0/49.5/33.5	60.0/57.0/54.5/37.0
External Static Pressure (ESP) Range	inWG		0-0.8	0-0.8	0-0.8	0-0.8	0-0.8	0-0.8
Indoor	Dimension (WxDxH)	inch	14.49x21.50x49.72	14.49x21.50x49.72	17.52x21.50x53.98	17.52x21.50x53.98	21.50x21.50x55.94	21.50x21.50x55.94
	Packing (WxDxH)	inch	17.52x31.10x52.95	17.52x31.10x52.95	20.47x31.10x57.09	20.47x31.10x57.09	25x31.10x59.84	25x31.10x59.84
	Net/Gross Weight	lbs.	123.02/154.76	123.02/154.76	149.25/182.10	149.25/182.10	186.51/232.14	186.51/232.14
Room Temperature	Cooling	°F	60-90	60-90	60-90	60-90	60-90	60-90
	Heating	°F	32-86	32-86	32-86	32-86	32-86	32-86
Liquid Side/Gas side	inch		3/8" / 3/4"	3/8" / 3/4"	3/8" / 3/4"	3/8" / 3/4"	3/8" / 3/4"	3/8" / 3/4"

OUTDOOR			CH-PQ18-230V0	CH-PQ24-230V0	CH-PQ33-230V0	CH-PQ36-230V0	CH-PQ48-230V0	CH-PQ55-230V0
Outdoor Model								
Power Supply	Rated	V, Ph, Hz	208-230, 1, 60	208-230, 1, 60	208-230, 1, 60	208-230, 1, 60	208-230, 1, 60	208-230, 1, 60
	Voltage range	V	187-253	187-253	187-253	187-253	187-253	187-253
Cooling	Rated Current	A	10.5	14	18	18	28	31
	Rated Capacity Range	Btu/h	4600-23100	6400-28700	11200-40000	14800-41700	18000-52000	11400-60000
Heating at 47°F	EER2		12.5	12	12	12	12	12
	SEER2		19	18.6	17.2	17.7	17.5	17.5
	Rated Capacity Range	Btu/h	5700-23100	6700-29100	9700-35800	10700-38400	13500-52000	8600-60000
	COP	W/W	3.6	3.49	3.54	3.6	3.28	3.35
	HSPF4		10.1	10	10.8	10	9.5	9.5
Heating at 5°F (-15°C)	HSPF5		8.5	8.1	8.8	8	7.7	7.7
	Rated Capacity	Btu/h	23600	25200	42500	39800	50000	54000
Minimum Circuit Ampacity (MCA)	A		16	19	29.5	26	38	40
Max. Fuse	A		20	20	30	30	40	40
Outdoor Air Flow (Max.)	CFM		1,765.8	1,765.8	3001.9	3001.9	3037.2	2648.7
Outdoor Noise Level	dB(A)		56.5	59	62	62.5	65	64.5
Outdoor Unit	Dimension (WxDxH)	inch	35.04 x 13.46 x 26.50	35.04 x 13.46 x 26.50	37.24 x 16.14 x 31.89	37.24 x 16.14 x 31.89	38.58 x 16.34 x 38.39	37.48 x 16.34 x 52.48
	Packing (WxDxH)	inch	39.17x15.67x29.13	39.17 x 15.67 x 29.13	42.91 x 19.68 x 34.84	42.91 x 19.68 x 34.84	45.08 x 19.68 x 42.52	43.11 x 19.49 x 58.27
Net/Gross Weight	lbs.		101.41/109.13	102.29/109.13	166.67/176.37	166.67/176.37	232.59/201.50	242.95/275.13
Refrigerant Type/Quantity	oz.		R454B/74.08	R454B/74.08	R454B/105.82	R454B/126.99	R454B/134.04	R454B/183.42
Refrigerant Precharge	ft.		25	25	25	25	25	25
Additional Charge for each ft.	oz./ft.		0.7	0.7	0.7	0.7	0.7	0.7
Design Pressure	PSIG		550/340	550/340	550/340	550/340	550/340	550/340
Refrigerant piping Liquid side/Gas Side	inch		3/8" / 3/4"	3/8" / 3/4"	3/8" / 3/4"	3/8" / 3/4"	3/8" / 3/4"	3/8" / 3/4"
Max. Pipe Length	ft.		164	164	164	213.2	246	246
Max. Difference in Level	ft.		82	82	82	98.4	98.4	98.4
Ambient Temperature	Cooling	ft.	-22-122	-22-122	-22-122	-22-122	-22-122	-22-122
	Heating	°F	-22-75	-22-75	-22-75	-22-75	-22-75	-22-75
Certifications	AHRI		✓	✓	✓	✓	✓	✓
	ETL		✓	✓	✓	✓	✓	✓
	Energy Star for Cold Climate		✓	✓	✓	✓	✓	✓
	NEEP		✓	✓	✓	✓	✓	✓

**NEW INVERTER TECHNOLOGY:** NEW Inverter Algorithm can analyze more factors, including temperature difference and the tendency of temperature difference changes, with a more frequent temperature detection to guarantee a more accurate and smooth control of the compressor output.

**EXTRAORDINARY COLD CLIMATE HEATING PERFORMANCE:** True high performance hyper units provide 100% heating output at 0°F.

**GOLD FIN:** Gold coating in the condenser withstands salty air, rain and other corrosive elements, preventing bacteria growth.


**DRAIN PAN HEATER:** Factory installed drain pan heater in outdoor unit prevents ice accumulation, improving heat transfer efficiency.

**ULTRA EFFICIENT DISCHARGE FAN:** The horizontal fan and vertical heat exchanger guarantee more uniform and efficient heat exchanging velocity across the entire heat exchanger surface, preventing frost on the compressor's coils.

**DELAY FUSE:** A detachable delay fuse added to the system protects the wire set from outdoor to indoor, preventing overcurrent.

# HYPER and REGULAR Series

UP TO  
**6**  
ZONES



**MULTI-ZONE**

*The newest generation of outdoor units now provide a wide range of compatibility across Cooper&Hunter's vast product selection to better serve any project configuration.*

# MULTI-ZONE Inverter Heat Pump Solutions

			WITHOUT SHUT-OFF VALVES					WITH SHUT-OFF VALVES				
			REGULAR					HYPER				
Outdoor Model			CH-R18MES-230VO	CH-R28MES-230VO	CH-R36MES-230VO	CH-R48MES-230VO	CH-R60MES-230VO	CH-RVHP19M-230VO	CH-RVHP28M-230VO	CH-RVHP36M-230VO	CH-RVHP48M-230VO	CH-RVHP55M-230VO
Power Supply	Rated	V, Ph, Hz	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60
	Voltage Range	V	187-253	187-253	187-253	187-253	187-253	187-253	187-253	187-253	187-253	187-253
Cooling	Rated Capacity (range)	Btu/h	5,400-21,600	7,200-32,000	9,000-42,000	12,000-55,000	19,000-62,000	5,400-28,000	7,200-37,000	9,000-43,000	12,000-57,000	19,000-59,000
	Rated Current	A	6	9.2	13.5	16.6	26.2	5.6	9.5	12	17.3	18.5
	EER2		14	13	12	12.5	10	15	12.5	13	12	12
	SEER2		25.1	25	24	24	22	25	23	23	23	22.2
Heating at 47°F	Rated Capacity (range)	Btu/h	5,700-21,600	8,400-29,000	10,000-42,500	13,000-53,000	20,000-60,000	5,700-27,000	8,400-36,000	10,000-44,000	13,000-57,000	20,000-59,000
	Rated Current	A	6.8	9.2	14	16.3	21	6.5	9.1	11.5	17.3	20.1
	COP	W/W	3.8	3.8	3.5	3.8	3.7	4	3.8	4	3.7	3.5
	HSPF4		9.8	9.5	9.5	10.3	9.5	10.4	10.5	10.7	11	10.5
	HSPF5		7.8	7	7	8	7.4	8.5	8.5	8.5	9	8.5
Heating at 5°F	Rated Capacity	Btu/h	13,500	19,000	26,000	36,000	39,000	19,000	27,000	36,000	47,000	47,000
Minimum Circuit Ampacity (Outdoor unit)	A		16	23	30.5	40	40	17.5	30	37	37	39.5
Max. Fuse (Outdoor unit)	A		20	25	35	45	45	20	35	40	40	40
Outdoor Air Flow (Max)	CFM		1,765.8	2,130.7	2,148.4	4,502.8	4,502.8	2,130.7	2,148.4	3,037.2	4,502.8	4,502.8
Outdoor Noise Level (Sound Pressure)	dB(A)		59.5	61	64.5	63	65	61.5	61	65	65	65
Dimension (WxDxH)	inch		35.04x13.46x26.50	37.24x16.14x31.89	37.24x16.14x31.89	37.48x16.34x52.48	37.48x16.34x52.48	37.24x16.14x31.89	37.24x16.14x31.89	38.58x16.34x38.39	37.48x16.34x52.48	37.48x16.34x52.48
Packing (WxDxH)	inch		40.55x17.24x29.53	42.91x19.68x34.84	42.91x19.68x34.84	43.11x19.49x58.27	43.11x19.49x58.27	42.91x19.68x34.84	42.91x19.68x34.84	45.08x19.68x42.52	43.11x19.49x58.27	43.11x19.49x58.27
Net/Gross Weight			100.53/109.35	138.89/149.69	168.87/180.12	222.00/254.19	237.88/270.28	137.35/148.15	168.43/179.67	211.86/244.71	246.47/276.68	246.47/276.68
Refrigerant Type/Charged	oz		R454B/61.73	R454B/84.66	R454B/120.63	R454B/148.15	R454B/151.68	R454B/78.31	R454B/120.63	R454B/134.04	R454B/151.68	R454B/151.68
Refrigerant Precharge	ft		75	100	125	150	150	75	100	125	150	150
Additional Charge for Each	oz/ft	0.16 for 1/4 in liquid pipe / *0.32 for 3/8 in liquid pipe	0.16 / 0.32	0.16 / 0.32	0.16 / 0.32	0.16 / 0.32	0.16 / 0.32	0.16 / 0.32	0.16 / 0.32	0.16 / 0.32	0.16 / 0.32	0.16 / 0.32
Design Pressure	PSIG		550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340	550/340
Refrigerant Piping	Liquid Side	inch	3 x 1/4"	4 x 1/4"	5 x 1/4"	6 x 1/4"	6 x 1/4"	3 x 1/4"	4 x 1/4"	5 x 1/4"	6 x 1/4"	6 x 1/4"
	Gas Side	inch	3 x 3/8"	3 x 3/8" + 1 x 1/2"	4 x 3/8" + 1 x 1/2"	4 x 3/8" + 2 x 1/2"	4 x 3/8" + 2 x 1/2"	3 x 3/8"	3 x 3/8" + 1 x 1/2"	3 x 3/8" + 2 x 1/2"	4 x 3/8" + 2 x 1/2"	4 x 3/8" + 2 x 1/2"
Max. Pipe Length	ft		196.8	262.4	262.4	262.4	262.4	196.8	262.4	262.4	262.4	262.4
Max. Length for One Indoor Unit	ft		98.4	114.8	114.8	114.8	114.8	98.4	114.8	114.8	114.8	114.8
Max. Height Difference in Level	ft		49.2	49.2	49.2	49.2	49.2	49.2	49.2	49.2	49.2	49.2
Max. Height Difference Between Indoor Units	ft		33	33	33	33	33	33	33	33	33	33
Ambient Temperature	Cooling	°F	-13-122	-13-122	-13-122	-13-122	-13-122	-22-122	-22-122	-22-122	-22-122	-22-122
	Heating	°F	-13-75	-13-75	-13-75	-13-75	-13-75	-22-75	-22-75	-22-75	-22-75	-22-75
Certification	AHRI		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Energy Star for Cold Climate		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	NEEP		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	ETL		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

Please note: These values represent outdoor units combined with the Astoria Indoor Wall Mounted Mini-Split. Values will vary depending on the combination of indoor units used.

Only units with Refrigerant Sensors work with Shut-off Valves

## REGULAR MULTI-ZONE Heat Pump Outdoor Unit

The C&H Multi-Zone systems with inverter technology are some of today's most advanced ductless split heat pumps. Up to 6 indoor units can be connected to a single outdoor unit, reducing the number of outdoor units required. All indoor units can be individually controlled and do not need to be installed at the same time.



## HYPER MULTI-ZONE Heat Pump Outdoor Unit

With our modern heat pump technology, the Hyper Heat series offers dependable cooling with the capability to heat in ambient temperatures as low as -22°F, making it an excellent energy-efficient solution for colder climates.



SCAN here to access our Multi-Unit Combination Guide



REGULAR



HYPER



CH-R18MES-230VO

UP TO  
**3**  
ZONES

Outdoor Model			CH-R18MES-230VO
Power Supply	Rated	V, Ph, Hz	208/230, 1, 60
	Voltage Range	V	187-253
Cooling	Rated Capacity (range)	Btu/h	5,400~21,600
	Rated Current	A	6
	EER2		14
	SEER2		25.1
	Rated Capacity (range)	Btu/h	5,700~21,600
Heating at 47°F	Rated Current	A	6.8
	COP	W/W	3.8
	HSPF4		9.8
	HSPF5		7.8
	Rated Capacity	Btu/h	13,500
Heating at 5°F	Rated Capacity	Btu/h	13,500
Minimum Circuit Ampacity (Outdoor unit)	A		16
Max. Fuse (Outdoor unit)	A		20
Outdoor Air Flow (Max)	CFM		1,765.8
Outdoor Noise Level (Sound Pressure)	dB(A)		59.5
Dimension (WxDxH)	inch		35.04x13.46x26.50
Packing (WxDxH)	inch		40.55x17.24x29.53
Net/Gross Weight			100.53/109.35
Refrigerant Type/Charged	oz		R454B/61.73
Refrigerant Precharge	ft		75
Additional Charge for Each	0.16 for 1/4 in liquid pipe / *0.32 for 3/8 in liquid pipe	oz/ft	0.16
Design Pressure	PSIG		550/340
Refrigerant Piping	Liquid Side	inch	3 x 1/4"
	Gas Side	inch	3 x 3/8"
Max. Pipe Length	ft		196.8
Max. Length for One Indoor Unit	ft		98.4
Max. Height Difference in Level	ft		49.2
Max. Height Difference Between Indoor Units	ft		33
Ambient Temperature	Cooling	°F	-13~122
	Heating	°F	-13~75
Certification	AHRI		✓
	Energy Star for Cold Climate		✓
	NEEP		✓
	ETL		✓

Multi-Zone Combination Charts on Pages 56-59




CH-R28MES-230VO

UP TO  
**4**  
ZONES


Outdoor Model			CH-R28MES-230VO
Power Supply	Rated	V, Ph, Hz	208/230, 1, 60
	Voltage Range	V	187-253
Cooling	Rated Capacity (range)	Btu/h	7,200~32,000
	Rated Current	A	9.2
	EER2		13
	SEER2		25
	Rated Capacity (range)	Btu/h	8,400~29,000
Heating at 47°F	Rated Current	A	9.2
	COP	W/W	3.8
	HSPF4		9.5
	HSPF5		7
	Rated Capacity	Btu/h	19,000
Heating at 5°F	Rated Capacity	Btu/h	19,000
Minimum Circuit Ampacity (Outdoor unit)	A		23
Max. Fuse (Outdoor unit)	A		25
Outdoor Air Flow (Max)	CFM		2,130.7
Outdoor Noise Level (Sound Pressure)	dB(A)		61
Dimension (WxDxH)	inch		37.24x16.14x31.89
Packing (WxDxH)	inch		42.91x19.68x34.84
Net/Gross Weight			138.89/149.69
Refrigerant Type/Charged	oz		R454B/61.73
Refrigerant Precharge	ft		100
Additional Charge for Each	0.16 for 1/4 in liquid pipe / *0.32 for 3/8 in liquid pipe	oz/ft	0.16
Design Pressure	PSIG		550/340
Refrigerant Piping	Liquid Side	inch	4 x 1/4"
	Gas Side	inch	3 x 3/8" + 1 x 1/2"
Max. Pipe Length	ft		262.4
Max. Length for One Indoor Unit	ft		114.8
Max. Height Difference in Level	ft		49.2
Max. Height Difference Between Indoor Units	ft		33
Ambient Temperature	Cooling	°F	-13~122
	Heating	°F	-13~75
Certification	AHRI		✓
	Energy Star for Cold Climate		✓
	NEEP		✓
	ETL		✓

Multi-Zone Combination Charts on Pages 56-59


ASTORIA



ASTORIA




OLIVIA




OLIVIA




ASTORIA



ASTORIA



OLIVIA



OLIVIA





**CH-R36MES-230VO**

UP TO  
**5**  
ZONES

Outdoor Model			CH-R36MES-230VO	
Power Supply	Rated	V, Ph, Hz	208/230, 1, 60	
	Voltage Range	V	187-253	
Cooling	Rated Capacity (range)	Btu/h	9,000-42,000	
	Rated Current	A	13.5	
	EER2		12	
	SEER2		24	
	Rated Capacity (range)	Btu/h	10,000-42,500	
Heating at 47°F	Rated Current	A	14	
	COP	W/W	3.5	
	HSPF4		9.5	
	HSPF5		7	
	Rated Capacity	Btu/h	26,000	
Heating at 5°F		Rated Capacity	Btu/h	26,000
Minimum Circuit Ampacity (Outdoor unit)		A	30.5	
Max. Fuse (Outdoor unit)		A	35	
Outdoor Air Flow (Max)		CFM	2,148.4	
Outdoor Noise Level (Sound Pressure)		dB(A)	64.5	
Dimension (WxDxH)		inch	37.24x16.14x31.89	
Packing (WxDxH)		inch	42.91x19.68x34.84	
Net/Gross Weight			168.87/180.12	
Refrigerant Type/Charged		oz	R454B/61.73	
Refrigerant Precharge		ft	125	
Additional Charge for Each	0.16 for 1/4 in liquid pipe / *0.32 for 3/8 in liquid pipe		oz/ft	0.16
Design Pressure		PSIG	550/340	
Refrigerant Piping	Liquid Side	inch	5 x 1/4"	
	Gas Side	inch	4 x 3/8" + 1 x 1/2"	
Max. Pipe Length		ft	262.4	
Max. Length for One Indoor Unit		ft	114.8	
Max. Height Difference in Level		ft	49.2	
Max. Height Difference Between Indoor Units		ft	33	
Ambient Temperature	Cooling	°F	-13-122	
	Heating	°F	-13-75	
Certification	AHRI		✓	
	Energy Star for Cold Climate		✓	
	NEEP		✓	
	ETL		✓	

Multi-Zone Combination Charts on Pages 56-59



**CH-R48MES-230VO**

UP TO  
**6**  
ZONES

Outdoor Model			CH-R48MES-230VO	
Power Supply	Rated	V, Ph, Hz	208/230, 1, 60	
	Voltage Range	V	187-253	
Cooling	Rated Capacity (range)	Btu/h	12,000-55,000	
	Rated Current	A	16.6	
	EER2		12.5	
	SEER2		24	
	Rated Capacity (range)	Btu/h	13,000-53,000	
Heating at 47°F	Rated Current	A	16.3	
	COP	W/W	3.8	
	HSPF4		10.3	
	HSPF5		8	
	Rated Capacity	Btu/h	36,000	
Heating at 5°F		Rated Capacity	Btu/h	36,000
Minimum Circuit Ampacity (Outdoor unit)		A	40	
Max. Fuse (Outdoor unit)		A	45	
Outdoor Air Flow (Max)		CFM	4,502.8	
Outdoor Noise Level (Sound Pressure)		dB(A)	63	
Dimension (WxDxH)		inch	37.48x16.34x52.48	
Packing (WxDxH)		inch	43.11x19.49x58.27	
Net/Gross Weight			222.00/254.19	
Refrigerant Type/Charged		oz	R454B/61.73	
Refrigerant Precharge		ft	150	
Additional Charge for Each	0.16 for 1/4 in liquid pipe / *0.32 for 3/8 in liquid pipe		oz/ft	0.16
Design Pressure		PSIG	550/340	
Refrigerant Piping	Liquid Side	inch	6 x 1/4"	
	Gas Side	inch	4 x 3/8" + 2 x 1/2"	
Max. Pipe Length		ft	262.4	
Max. Length for One Indoor Unit		ft	114.8	
Max. Height Difference in Level		ft	49.2	
Max. Height Difference Between Indoor Units		ft	33	
Ambient Temperature	Cooling	°F	-13-122	
	Heating	°F	-13-75	
Certification	AHRI		✓	
	Energy Star for Cold Climate		✓	
	NEEP		✓	
	ETL		✓	

Multi-Zone Combination Charts on Pages 56-59



# REGULAR COMPRESSORS



UP TO  
**6**  
ZONES

**CH-R60MES-230VO**



Outdoor Model		CH-R60MES-230VO	
Power Supply	Rated	V, Ph, Hz	208/230, 1, 60
	Voltage Range	V	187-253
Cooling	Rated Capacity (range)	Btu/h	19,000-62,000
	Rated Current	A	26.2
	EER2		10
	SEER2		22
Heating at 47°F	Rated Capacity (range)	Btu/h	20,000-60,000
	Rated Current	A	21
	COP	W/W	3.7
	HSPF4		9.5
	HSPF5		7.4
Heating at 5°F	Rated Capacity	Btu/h	39,000
Minimum Circuit Ampacity (Outdoor unit)		A	40
Max. Fuse (Outdoor unit)		A	45
Outdoor Air Flow (Max)		CFM	4,502.8
Outdoor Noise Level (Sound Pressure)		dB(A)	65
Dimension (WxDxH)		inch	37.48x16.34x52.48
Packing (WxDxH)		inch	43.11x19.49x58.27
Net/Gross Weight			237.88/270.28
Refrigerant Type/Charged		oz	R454B/61.73
Refrigerant Precharge		ft	150
Additional Charge for Each	0.16 for 1/4 in liquid pipe / *0.32 for 3/8 in liquid pipe	oz/ft	0.16
Design Pressure		PSIG	550/340
Refrigerant Piping	Liquid Side	inch	6 x 1/4"
	Gas Side	inch	4 x 3/8" + 2 x 1/2"
Max. Pipe Length		ft	262.4
Max. Length for One Indoor Unit		ft	114.8
Max. Height Difference in Level		ft	49.2
Max. Height Difference Between Indoor Units		ft	33
Ambient Temperature	Cooling	°F	-13-122
	Heating	°F	-13-75
Certification	AHRI		✓
	Energy Star for Cold Climate		✓
	NEEP		✓
	ETL		✓

Multi-Zone Combination Charts on Pages 56-59

# INVERTER TECHNOLOGY *Simplified*

Inverter technology is a type of technology used in heat pump outdoor units allowing the compressor to run at variable speeds, rather than just on or off. The heat pump can adjust its output to match the heating or cooling needs of the space it is serving, leading to increased efficiency and energy savings.



Inverter technology uses a device called the variable frequency drive (VFD) to control the frequency of the incoming electrical current that goes to the appliance. The VFD contains a small part called an inverter that converts the AC power supplied by house sockets to DC. While the energy flow is still in DC, it gives an opportunity for the VFD to change the frequency from the standard 60Hz to whatever power is needed by the appliance's motor. In addition, inverter technology uses a process called "flash injection" to allow the heat pump to produce superior heating. The flash injection process uses a bypass circuit to reroute a portion of the refrigerant to two places. Hot refrigerant flows back to the indoor coil to enhance heating. Colder refrigerant is injected back into the compressor to allow it to run at faster speeds to produce high-performance heat exchange. This technology also guarantees quiet and efficient operation for outdoor and indoor units.

This process of conserving energy by using less power, while still delivering better results is achieved through constant movement, which can save up to **40%** of energy consumption.

The efficiency of inverter technology also extends into the longevity of the unit and low maintenance, all thanks to the unit running under low demand.





CH-RVHP19M-230VO

UP TO  
**3**  
ZONES

Outdoor Model			CH-RVHP19M-230VO	
Power Supply	Rated	V, Ph, Hz	208/230, 1, 60	
	Voltage Range	V	187-253	
Cooling	Rated Capacity (range)	Btu/h	5,400~28,000	
	Rated Current	A	5.6	
	EER2		15	
	SEER2		25	
	Rated Capacity (range)	Btu/h	5,700~27,000	
Heating at 47°F	Rated Current	A	6.5	
	COP	W/W	4	
	HSPF4		10.4	
	HSPF5		8.5	
	Rated Capacity	Btu/h	19,000	
Heating at 5°F		Rated Capacity	Btu/h	19,000
Minimum Circuit Ampacity (Outdoor unit)		A	17.5	
Max. Fuse (Outdoor unit)		A	20	
Outdoor Air Flow (Max)		CFM	2,130.7	
Outdoor Noise Level (Sound Pressure)		dB(A)	61.5	
Dimension (WxDxH)		inch	37.24x16.14x31.89	
Packing (WxDxH)		inch	42.91x19.68x34.84	
Net/Gross Weight			137.35/148.15	
Refrigerant Type/Charged		oz	R454B/78.31	
Refrigerant Precharge		ft	75	
Additional Charge for Each		0.16 for 1/4 in liquid pipe / *0.32 for 3/8 in liquid pipe oz/ft	0.16	
Design Pressure		PSIG	550/340	
Refrigerant Piping	Liquid Side	inch	3 x 1/4"	
	Gas Side	inch	3 x 3/8"	
Max. Pipe Length		ft	196.8	
Max. Length for One Indoor Unit		ft	98.4	
Max. Height Difference in Level		ft	49.2	
Max. Height Difference Between Indoor Units		ft	33	
Ambient Temperature	Cooling	°F	-22~122	
	Heating	°F	-22~75	
Certification	AHRI		✓	
	Energy Star for Cold Climate		✓	
	NEEP		✓	
	ETL		✓	

Multi-Zone Combination Charts on Pages 56-59



CH-RVHP28M-230VO

UP TO  
**4**  
ZONES

Outdoor Model			CH-RVHP28M-230VO	
Power Supply	Rated	V, Ph, Hz	208/230, 1, 60	
	Voltage Range	V	187-253	
Cooling	Rated Capacity (range)	Btu/h	7,200~37,000	
	Rated Current	A	9.5	
	EER2		12.5	
	SEER2		23	
	Rated Capacity (range)	Btu/h	8,400~36,000	
Heating at 47°F	Rated Current	A	9.1	
	COP	W/W	3.8	
	HSPF4		10.5	
	HSPF5		8.5	
	Rated Capacity	Btu/h	27,000	
Heating at 5°F		Rated Capacity	Btu/h	27,000
Minimum Circuit Ampacity (Outdoor unit)		A	30	
Max. Fuse (Outdoor unit)		A	35	
Outdoor Air Flow (Max)		CFM	2,148.4	
Outdoor Noise Level (Sound Pressure)		dB(A)	61	
Dimension (WxDxH)		inch	37.24x16.14x31.89	
Packing (WxDxH)		inch	42.91x19.68x34.84	
Net/Gross Weight			168.43/179.67	
Refrigerant Type/Charged		oz	R454B/120.63	
Refrigerant Precharge		ft	100	
Additional Charge for Each		0.16 for 1/4 in liquid pipe / *0.32 for 3/8 in liquid pipe oz/ft	0.16	
Design Pressure		PSIG	550/340	
Refrigerant Piping	Liquid Side	inch	4 x 1/4"	
	Gas Side	inch	3 x 3/8" + 1 x 1/2"	
Max. Pipe Length		ft	262.4	
Max. Length for One Indoor Unit		ft	114.8	
Max. Height Difference in Level		ft	49.2	
Max. Height Difference Between Indoor Units		ft	33	
Ambient Temperature	Cooling	°F	-22~122	
	Heating	°F	-22~75	
Certification	AHRI		✓	
	Energy Star for Cold Climate		✓	
	NEEP		✓	
	ETL		✓	

Multi-Zone Combination Charts on Pages 56-59





**CH-RVHP36M-230VO**

UP TO  
**5**  
ZONES

Outdoor Model			CH-RVHP36M-230VO	
Power Supply	Rated	V, Ph, Hz	208/230, 1, 60	
	Voltage Range	V	187-253	
Cooling	Rated Capacity (range)	Btu/h	9,000-43,000	
	Rated Current	A	12	
	EER2		13	
	SEER2		23	
	Rated Capacity (range)	Btu/h	10,000-44,000	
Heating at 47°F	Rated Current	A	11.5	
	COP	W/W	4	
	HSPF4		10.7	
	HSPF5		8.5	
	Rated Capacity	Btu/h	36,000	
Heating at 5°F		Rated Capacity	Btu/h	36,000
Minimum Circuit Ampacity (Outdoor unit)		A	37	
Max. Fuse (Outdoor unit)		A	40	
Outdoor Air Flow (Max)		CFM	3,037.2	
Outdoor Noise Level (Sound Pressure)		dB(A)	65	
Dimension (WxDxH)		inch	38.58x16.34x38.39	
Packing (WxDxH)		inch	45.08x19.68x42.52	
Net/Gross Weight			211.86/244.71	
Refrigerant Type/Charged		oz	R454B/134.04	
Refrigerant Precharge		ft	125	
Additional Charge for Each		0.16 for 1/4 in liquid pipe / *0.32 for 3/8 in liquid pipe oz/ft	0.16	
Design Pressure		PSIG	550/340	
Refrigerant Piping	Liquid Side	inch	5 x 1/4"	
	Gas Side	inch	3 x 3/8" + 2 x 1/2"	
Max. Pipe Length		ft	262.4	
Max. Length for One Indoor Unit		ft	114.8	
Max. Height Difference in Level		ft	49.2	
Max. Height Difference Between Indoor Units		ft	33	
Ambient Temperature	Cooling	°F	-22-122	
	Heating	°F	-22-75	
Certification	AHRI		✓	
	Energy Star for Cold Climate		✓	
	NEEP		✓	
	ETL		✓	

Multi-Zone Combination Charts on Pages 56-59



**CH-RVHP48M-230VO**

UP TO  
**6**  
ZONES

Outdoor Model			CH-RVHP48M-230VO	
Power Supply	Rated	V, Ph, Hz	208/230, 1, 60	
	Voltage Range	V	187-253	
Cooling	Rated Capacity (range)	Btu/h	12,000-57,000	
	Rated Current	A	17.3	
	EER2		12	
	SEER2		23	
	Rated Capacity (range)	Btu/h	13,000-57,000	
Heating at 47°F	Rated Current	A	17.3	
	COP	W/W	3.7	
	HSPF4		11	
	HSPF5		9	
	Rated Capacity	Btu/h	47,000	
Heating at 5°F		Rated Capacity	Btu/h	47,000
Minimum Circuit Ampacity (Outdoor unit)		A	37	
Max. Fuse (Outdoor unit)		A	40	
Outdoor Air Flow (Max)		CFM	4,502.8	
Outdoor Noise Level (Sound Pressure)		dB(A)	65	
Dimension (WxDxH)		inch	37.48x16.34x52.48	
Packing (WxDxH)		inch	43.11x19.49x58.27	
Net/Gross Weight			246.47/276.68	
Refrigerant Type/Charged		oz	R454B/151.68	
Refrigerant Precharge		ft	150	
Additional Charge for Each		0.16 for 1/4 in liquid pipe / *0.32 for 3/8 in liquid pipe oz/ft	0.16	
Design Pressure		PSIG	550/340	
Refrigerant Piping	Liquid Side	inch	6 x 1/4"	
	Gas Side	inch	4 x 3/8" + 2 x 1/2"	
Max. Pipe Length		ft	262.4	
Max. Length for One Indoor Unit		ft	114.8	
Max. Height Difference in Level		ft	49.2	
Max. Height Difference Between Indoor Units		ft	33	
Ambient Temperature	Cooling	°F	-22-122	
	Heating	°F	-22-75	
Certification	AHRI		✓	
	Energy Star for Cold Climate		✓	
	NEEP		✓	
	ETL		✓	

Multi-Zone Combination Charts on Pages 56-59



# HYPER COMPRESSORS




CH-RVP55M-230VO

UP TO  
**6**  
ZONES



Outdoor Model		CH-RVHP55M-230VO	
Power Supply	Rated	V, Ph, Hz	208/230, 1, 60
	Voltage Range	V	187-253
Cooling	Rated Capacity (range)	Btu/h	19,000-59,000
	Rated Current	A	18.5
	EER2		12
	SEER2		22.2
	Rated Capacity (range)	Btu/h	20,000-59,000
Heating at 47°F	Rated Current	A	20.1
	COP	W/W	3.5
	HSPF4		10.5
	HSPF5		8.5
	Rated Capacity	Btu/h	47,000
Heating at 5°F		Rated Capacity	Btu/h
Minimum Circuit Ampacity (Outdoor unit)		A	39.5
Max. Fuse (Outdoor unit)		A	40
Outdoor Air Flow (Max)		CFM	4,502.8
Outdoor Noise Level (Sound Pressure)		dB(A)	65
Dimension (WxDxH)		inch	37.48x16.34x52.48
Packing (WxDxH)		inch	43.11x19.49x58.27
Net/Gross Weight			246.47/276.68
Refrigerant Type/Charged		oz	R454B/151.68
Refrigerant Precharge		ft	150
Additional Charge for Each		0.16 for 1/4 in liquid pipe / *0.32 for 3/8 in liquid pipe	oz/ft
Design Pressure		PSIG	550/340
Refrigerant Piping	Liquid Side	inch	6 x 1/4"
	Gas Side	inch	4 x 3/8" + 2 x 1/2"
Max. Pipe Length		ft	262.4
Max. Length for One Indoor Unit		ft	114.8
Max. Height Difference in Level		ft	49.2
Max. Height Difference Between Indoor Units		ft	33
Ambient Temperature	Cooling	°F	-22-122
	Heating	°F	-22-75
Certification	AHRI		✓
	Energy Star for Cold Climate		✓
	NEEP		✓
	ETL		✓

Multi-Zone Combination Charts on Pages 56-59

ASTORIA



ASTORIA



OLIVIA



OLIVIA



Proud Sponsors





# COMBINATION CHART

## MULTI-ZONE COMBINATION GUIDE



UP TO 6 ZONES



CH-RVHP48M-230VO  
CH-RVHP55M-230VO

Btu/h	Astoria Astoria Pro	Olivia	Olivia Midnight	Ceiling Cassette Ceiling Cassette Pro	One-Way Cassette	Slim Duct	New Console	Floor Ceiling	Multi-Position Air Handler
6K	CH-RH06MASTWM-230VI CH-PRO06MASTWM-230VI	CH-R06MOLVWM-230VII	CH-RB06MOLVWM-230VI						
9K	CH-RH09MASTWM-230VI CH-PRO09MASTWM-230VI	CH-R09MOLVWM-230VI	CH-RB09MOLVWM-230VI	CH-RH09MCT CH-RSH09-12MCT	CH-RSH06-12MCT1W	CH-RS06-12MDT-MS	CH-RSH09MMC		
12K	CH-RH12MASTWM-230VI CH-PRO12MASTWM-230VI	CH-R12MOLVWM-230VI	CH-RB12MOLVWM-230VI	CH-RH12MCT CH-RSH09-12MCT			CH-RSH12MMC		
18K	CH-RH18MASTWM-230VI CH-PRO18MASTWM-230VI	CH-R18MOLVWM-230VI	CH-RB18MOLVWM-230VI	CH-RH18MCT CH-RSH18MCT	CH-RSH18MCT1W	CH-RS18MDT-MS	CH-RSH16MMC*	CH-RSH18MFC	CH-RS18MAHU
24K	CH-RH24MASTWM-230VI CH-PRO24MASTWM-230VI	CH-R24MOLVWM-230VI	CH-RB24MOLVWM-230VI	CH-RH24MCT CH-RSH24MCT		CH-RS24MDT-HS		CH-RSH24MFC	CH-RS24MAHU
30K	CH-RH30MASTWM-230VI CH-PRO30MASTWM-230VI	CH-R30MOLVWM-230VI							CH-RS30MAHU
36K	CH-RH36MASTWM-230VI CH-PRO36MASTWM-230VI	CH-R36MOLVWM-230VI							

\*This unit also available in 15K  
CH-RH15MASTWM-230VI / CH-PRO15MASTWM-230VI

• Minimum of two zones must be connected • Minimum line length required per zone is 10 ft. • Port adapters are included with outdoor units, branch boxes not required

Model Name	Ducted	Min. Circuit Ampacity (MCA)	Max. Fuse Size	Cooling at 95° F						Heating at 47° F						Refrigerant		Refrigerant Piping						Ambient Temperature	
				Capacity (range)	Input (range)	Rated current (range)	SEER2	EER2	Capacity (range)	Input (range)	Rated current (range)	COP	HSPF4	HSPF5	Noise Level	Precharge	Liquid side	Gas side	Max. length for all rooms	Max. length for one indoor unit	Max. height elevation between indoor and outdoor	Max. height elevation between indoor units	Cooling	Heating	
CH-RVHP19M-230VO	Ducted	17.5	20	19,000(5,400-27,600)	1,460(400-2,350)	7.5(3.5-11)	20	13	20,000(5,700-25,400)	1,460(400-2,350)	7.5(3.5-11)	4	10	8	61.5	75	3x1/4"	3x3/8"	196.8	98.4	49.2	33	-22-122	-22-75	
CH-RVHP28M-230VO	Non-Ducted	17.5	20	19,000(5,400-28,000)	1,265(400-2,250)	5.6(3.5-10)	25	15	20,000(5,700-27,000)	1,265(400-2,250)	5.6(3.5-10)	4	10.4	8.5	61.5	75	3x1/4"	3x3/8"	196.8	98.4	49.2	33	-22-122	-22-75	
CH-RVHP36M-230VO	Ducted	30	35	28,000(7,200-38,000)	2,333(500-4,500)	10.5(4-20)	19	12	28,000(8,400-38,500)	2,333(500-4,500)	10.5(4-20)	3.6	9.5	7.7	61	100	4x1/4"	3x3/8"x1/2"	262.4	114.8	49.2	33	-22-122	-22-75	
CH-RVHP48M-230VO	Non-Ducted	30	35	27,000(7,200-37,000)	2,125(500-3,620)	9.5(4-16)	23	12.5	27,000(8,400-36,000)	2,125(500-3,620)	9.5(4-16)	3.8	10.5	8.5	61	100	4x1/4"	3x3/8"x1/2"	262.4	114.8	49.2	33	-22-122	-22-75	
CH-RVHP55M-230VO	Ducted	37	40	36,000(9,000-42,000)	3,000(600-4,200)	13.4(5.2-19)	19.4	12	36,000(10,000-45,000)	3,000(600-4,200)	13.4(5.2-19)	3.8	10.4	8.8	65	125	5x1/4"	3x3/8"x21/2"	262.4	114.8	49.2	33	-22-122	-22-75	
CH-RVHP55M-230VO	Non-Ducted	37	40	36,000(9,000-43,000)	2,750(600-4,000)	12(5.2-17.8)	23	13	36,000(10,000-44,000)	2,750(600-4,000)	12(5.2-17.8)	4	10.7	8.5	65	125	5x1/4"	3x3/8"x21/2"	262.4	114.8	49.2	33	-22-122	-22-75	
CH-RVHP48M-230VO	Ducted	37	40	47,000(12,000-57,000)	4,020(800-5,700)	17.9(7-25)	20.4	11.7	48,000(13,000-60,000)	4,020(800-5,700)	17.9(7-25)	3.5	11	9	65	150	6x1/4"	4x3/8"x21/2"	262.4	114.8	49.2	33	-22-122	-22-75	
CH-RVHP48M-230VO	Non-Ducted	37	40	47,000(12,000-57,000)	3,917(800-5,400)	17.3(7-24)	23	12	49,000(13,000-57,000)	3,917(800-5,400)	17.3(7-24)	3.7	11	9	65	150	6x1/4"	4x3/8"x21/2"	262.4	114.8	49.2	33	-22-122	-22-75	
CH-RVHP55M-230VO	Ducted	39.5	40	53,000(19,000-60,000)	4,530(1,200-6,100)	21(10-27)	20	11.7	55,000(20,000-61,000)	4,530(1,200-6,100)	21(10-27)	3.7	10.7	8.8	65	150	6x1/4"	4x3/8"x21/2"	262.4	114.8	49.2	33	-22-122	-22-75	
CH-RVHP55M-230VO	Non-Ducted	39.5	40	51,000(19,000-59,000)	4,250(1,200-5,400)	18.5(10.5-24)	22.2	12	55,000(20,000-59,000)	4,250(1,200-5,400)	18.5(10.5-24)	3.5	10.5	8.5	65	150	6x1/4"	4x3/8"x21/2"	262.4	114.8	49.2	33	-22-122	-22-75	

UP TO 3 ZONES



CH-RVHP19M-230VO

2 ZONES
6K 6K
6K 9K
6K 12K
6K 18K
6K 24K
9K 9K
9K 12K
9K 18K
9K 24K
12K 12K
12K 18K
12K 24K
18K 18K

3 ZONES
6K 6K 6K
6K 6K 9K
6K 6K 12K
6K 6K 18K
6K 6K 24K
6K 9K 9K
6K 9K 12K
6K 9K 18K
6K 12K 12K
6K 12K 18K
9K 9K 9K
9K 9K 12K
9K 9K 18K
9K 12K 12K
12K 12K 12K

UP TO 4 ZONES



CH-RVHP28M-230VO

2 ZONES	2 ZONES
6K 18K	
9K 24K	
6K 24K	
9K 9K	
9K 12K	
9K 18K	
12K 12K	
12K 18K	

3 ZONES
6K 6K 6K
6K 6K 9K
6K 6K 12K
6K 6K 18K
6K 6K 24K
6K 9K 9K
6K 9K 12K
6K 9K 18K
6K 12K 12K
6K 12K 18K
6K 12K 24K
6K 18K 18K
12K 18K 18K

3 ZONES	3 ZONES
6K 18K 24K	
9K 9K 9K	
9K 9K 12K	
9K 9K 18K	
9K 12K 12K	
9K 12K 18K	
9K 12K 24K	
12K 12K 12K	
12K 12K 18K	
12K 12K 24K	
12K 18K 18K	

4 ZONES	4 ZONES
6K 6K 6K 6K	
6K 6K 6K 9K	
6K 6K 6K 12K	
6K 6K 6K 18K	
6K 6K 6K 24K	
6K 6K 9K 9K	
6K 6K 9K 12K	
6K 6K 9K 18K	
6K 6K 9K 24K	
6K 6K 12K 12K	
6K 6K 12K 18K	
6K 6K 12K 24K	
6K 6K 18K 18K	
6K 6K 18K 24K	
6K 9K 9K 9K	
6K 9K 9K 12K	
6K 9K 9K 18K	
6K 9K 9K 24K	
6K 9K 12K 12K	
6K 9K 12K 18K	
6K 9K 12K 24K	
6K 9K 18K 18K	
6K 9K 18K 24K	
6K 12K 12K 12K	
6K 12K 12K 18K	
6K 12K 12K 24K	
6K 12K 18K 18K	
6K 12K 18K 24K	
6K 18K 18K 18K	
6K 18K 18K 24K	
9K 9K 9K 9K	
9K 9K 9K 12K	
9K 9K 9K 18K	
9K 9K 9K 24K	
9K 12K 12K 12K	
9K 12K 12K 18K	
9K 12K 12K 24K	
9K 12K 18K 18K	
9K 12K 18K 24K	
9K 18K 18K 18K	
9K 18K 18K 24K	
12K 12K 12K 12K	
12K 12K 12K 18K	
12K 12K 12K 24K	
12K 12K 18K 18K	
12K 12K 18K 24K	
12K 18K 18K 18K	
12K 18K 18K 24K	

UP TO 5 ZONES



CH-RVHP36M-230VO

2 ZONES
6K 18K
6K 24K
6K 30K
6K 36K
9K 18K
9K 24K
9K 30K
9K 36K
12K 12K
12K 18K
12K 24K
12K 30K
12K 36K
18K 18K
18K 24K
18K 30K
24K 24K

3 ZONES	3 ZONES
6K 6K 12K	
6K 6K 18K	
6K 6K 24K	
6K 6K 30K	
6K 6K 36K	
6K 9K 9K	
6K 9K 12K	
6K 9K 18K	
6K 9K 24K	
6K 9K 30K	
6K 12K 12K	
6K 12K 18K	
6K 12K 24K	
6K 12K 30K	
6K 18K 18K	
6K 18K 24K	

4 ZONES	4 ZONES	4 ZONES
6K 6K 6K 6K		
6K 6K 6K 9K		
6K 6K 6K 12K		
6K 6K 6K 18K		
6K 6K 6K 24K		
6K 6K 9K 9K		
6K 6K 9K 12K		
6K 6K 9K 18K		
6K 6K 9K 24K		
6K 6K 12K 12K		
6K 6K 12K 18K		
6K 6K 12K 24K		
6K 6K 18K 18K		
6K 6K 18K 24K		
6K 9K 9K 9K		
6K 9K 9K 12K		
6K 9K 9K 18K		
6K 9K 9K 24K		
6K 9K 12K 12K		
6K 9K 12K 18K		
6K 9K 12K 24K		
6K 9K 18K 18K		
6K 9K 18K 24K		
9K 9K 9K 9K		
9K 9K 9K 12K		
9K 9K 9K 18K		
9K 9K 9K 24K		
9K 12K 12K 12K		
9K 12K 12K 18K		
9K 12K 12K 24K		
9K 12K 18K 18K		
9K 12K 18K 24K		
9K 18K 18K 18K		
9K 18K 18K 24K		

5 ZONES
6K 6K 6K 6K 6K
6K 6K 6K 6K 9K
6K 6K 6K 6K 12K
6K 6K 6K 6K 18K
6K 6K 6K 6K 24K
6K 6K 6K 9K 9K
6K 6K 6K 9K 12K
6K 6K 6K 9K 18K
6K 6K 6K 9K 24K
6K 6K 6K 12K 12K
6K 6K 6K 12K 18K
6K 6K 6K 12K 24K
6K 6K 6K 18K 18K
6K 6K 6K 18K 24K
6K 6K 9K 9K 9K
6K 6K 9K 9K 12K
6K 6K 9K 9K 18K
6K 6K 9K 9K 24K
6K 6K 9K 12K 12K
6K 6K 9K 12K 18K
6K 6K 9K 12K 24K
6K 6K 9K 18K 18K
6K 6K 9K 18K 24K
6K 9K 9K 9K 9K
6K 9K 9K 9K 12K
6K 9K 9K 9K 18K
6K 9K 9K 9K 24K
6K 9K 12K 12K 12K
6K 9K 12K 12K 18K
6K 9K 12K 12K 24K
6K 9K 12K 18K 18K
6K 9K 12K 18K 24K
6K 9K 18K 18K 18K
6K 9K 18K 18K 24K

2 ZONES
6K 18K
6K 24K
6K 30K
6K 36K
9K 18K
9K 24K
9K 30K
9K 36K
12K 12K
12K 18K
12K 24K
12K 30K
12K 36K
18K 18K
18K 24K
18K 30K
18K 36K
24K 24K
24K 30K
24K 36K

3 ZONES	3 ZONES
6K 6K 18K	
6K 6K 24K	
6K 6K 30K	
6K 6K 36K	
6K 9K 9K	
6K 9K 12K	
6K 9K 18K	
6K 9K 24K	
6K 9K 30K	
6K 9K 36K	
6K 12K 12K	
6K 12K 18K	
6K 12K 24K	
6K 12K 30K	
6K 12K 36K	
6K 18K 18K	
6K 18K 24K	
6K 18K 30K	
6K 18K 36K	
9K 9K 9K	
9K 9K 12K	
9K 9K 18K	
9K 9K 24K	
9K 9K 30K	
9K 9K 36K	

3 ZONES	3 ZONES
9K 9K 24K	
9K 9K 30K	
9K 9K 36K	
9K 12K 12K	
9K 12K 18K	
9K 12K 24K	
9K 12K 30K	
9K 12K 36K	
9K 18K 18K	
9K 18K 24K	
9K 18K 30K	
9K 18K 36K	
12K 12K 12K	
12K 12K 18K	
12K 12K 24K	
12K 12K 30K	
12K 12K 36K	
12K 18K 18K	
12K 18K 24K	
12K 18K 30K	
12K 18K 36K	
18K 18K 18K	
18K 18K 24K	
18K 18K 30K	
18K 18K 36K	



## MONOBLOCK

HOTELS | MOTELS | ASSISTED LIVING FACILITIES | CLINICS | OFFICES | CLASSROOMS

# PTAC

## Packaged Terminal Air Conditioner Heat Pump



**UP TO 11.4 EER2**  
9K, 12K, 15K Btu/h

- Auto Restart
- Fresh Air Ventilation
- Auto Defrost
- LED Display
- Digital Temperature Control
- Smart Kit Built in
- Constant Fan Function



(See Accessories PG 64)


### CONTROL OPTIONS

- Smart Kit ready with Downloadable C&H Remote app
- Remote Control included




Customer Model			CH-PTW-09HPGF	CH-PTW-12HPGF	CH-PTW-HE15HP
Power Supply		V-Ph-Hz	208/230,1, 60	208/230,1, 60	208/230,1, 60
Cooling	Rated Capacity	Btu/h	9,300/9,200	12,000/11,800	14,700/14,500
	Input	W	820/810	1,040/1,020	1,390/1,370
	Current	A	4.2/4.6	5.3/5.8	6.5/7.4
	EER2		11.4	10.5	10.6
Heating (PTC)	Capacity	Btu/h	10,900/8,900	10,900/8,900	10,900/8,900
	Input(Heater)	W	3,500/2,897	3,500/2,897	3,500/2,897
	Current	A	15.3/13.7	15.3/13.7	15.3/13.7
Heating (Heat pump)	Capacity	Btu/h	8,100/7,900	10,800/10,500	13,500/13,200
	Input	W	720/690	890/850	1,170/1,120
	Current	A	3.9/4.3	5.0/5.3	6.0/6.4
	COP	W/W	3.4	3.2	3.2
Indoor Air Flow (Hi/Lo)		CMF	362.9/300	438/344	416/330
Indoor Noise Level (Hi/Lo)		dB(A)	50/49.5	52/51.5	53/52.5
Outdoor Noise Level (Hi)		dB(A)	64	67	67
Refrigerant Type		Refrigerant type	R32	R32	R32
		oz	15.17	26.81	31.75
Design Pressure (Lo/Hi)		psi	300/580	300/580	300/580
OperationTemp	Indoor (Cooling/Heating)	°F	62°F-90°F/32°F-80°F	62°F-90°F/32°F-80°F	62°F-90°F/32°F-80°F
	Outdoor (Cooling/Heating)	°F	64°F-109°F/23°F-76°F	64°F-109°F/23°F-76°F	64°F-109°F/23°F-76°F
Dimension (WxDxH)		in	42x21x16	42x21x16	42x21x16
Packing (WxDxH)		in	44.5x25x19.3	44.5x25x19.3	44.5x25x19.3
Net/Gross Weight		lbs	99.2/108	110.2/119	113.5/122

## PTAC Components




## PTAC Optional Accessories

- Foldable Wall Sleeve
- Architectural Grille



## PTAC Controls *Choose which control option works for you\**



(See Accessories PG 64)

# ACCESSORIES

Our bundled installation kit offers ease and convenience for HVAC technicians while providing a long-lasting, quality product that customers will not have to replace.

Installation Kit includes one of each: 16ft Pre-Flared and Insulated Copper Line Set, 16ft Communication Wires between Indoor and Outdoor unit, Small Accessories and a 16ft Drainage Extension.

- 99.9% Copper (ASTM B-280)
- Pre-insulated (ASTM D154)
- UV & UV-C Protected
- Pre-flared

## Smart KIT

The Cooper&Hunter Smart Kit includes an Easy-to-Install USB adapter that connects inside the unit to enable wireless remote control function for Wall Mounted Mini Split Units. In addition, when used with the downloadable C&H Remote App, the units can be controlled with any smart device from any location. The Smart Kit is compatible with the Astoria, Olivia, Olivia Midnight and Mia indoor units.



## Remote Control Devices

This newly designed remote control is specifically utilized with the PTAC Units. The LCD screen will display basic functions on this controller including Mode, Temperature Control, Timer, and Fan Speed. A small sensor located on the back of the control will read the room temperature and adjust the settings accordingly.



PTAC Remote Control

Our newest Remote Control has the capability of operating most of the Cooper&Hunter indoor Mini Splits in both, Single and Multi-Zones. Its advanced technology allows for additional functions, such as Eco Mode, Breeze Away, Self Cleaning Mode, Sleep Mode, Follow Me Mode, Turbo and Lock mode. Functions to control horizontal and vertical the swing of louvers is also included in this Remote.



C&H Universal Control

## Smart Wired Thermostat

In addition to the features offered in the wired thermostat, the feature that sets the new 12V wall thermostat apart from the previous models is its ability to connect to the internet and provide compatible units with remote connectivity through the Cooper&Hunter App, allowing you to control your air conditioning your smartphone or tablet, wherever you are.



120N

## Auxiliary Heater

The Auxiliary Heater is an optional device that is purchased separately as a back-up heating option for indoor units in case of an emergency or when the primary heating system is not working. The optional auxiliary heater has allows for the AHU unit to be used as a Heater or Heater+Heat Pump and is available in 5kW, 10kW, 15kW, and 20 kW models.



**AHU**  
CH-NREH05KW  
CH-NREH10KW  
CH-NREH15KW  
CH-NREH20KW

**PEAQ**  
CH-PQEH05KW  
CH-PQEH10KW  
CH-PQEH15KW  
CH-PQEH20KW

## 12' Mini Split Line Set Cover Kit

The 3" and 4" Line Set Cover Kit is designed to protect and hide mini split refrigerant lines. This material is lightweight and weatherproof, yet ultra durable and easy to install and can be installed over existing pre-installed pipes.

Cover Kit includes:

- 1 x 120" flat swivel elbow
- 4 x straight ducts
- 3 x couplers
- 1 x end fitting
- 1 x 90° elbow
- 1 x wall inlet



CH-3LNCS12 | CH-4LNCS12

## Outdoor Wall Mounting Bracket

Mount your outdoor condenser on the wall to protect it from severe weather conditions like heavy snow or flooding.

- Maximum weight load: 441 lbs.
- Weather-proof powder-coated surface
- Includes installation bolts and rubber anti-vibration pads



CH-H22

## PTAC Sleeve & Grille

The standard size (41" 7/8 x 16" 3/8 x 14" 3/4) PTAC Foldable Metal Wall Sleeve is designed especially for Cooper&Hunter PTACs. This wall sleeve is insulated for thermal efficiency and noise reduction. Its white powder coating matches C&H's PTAC units and is made of galvanized zinc coated steel for exceptional durability. Condensate Drain Kit is included.



AB-PTSLV

Keep your PTAC unit running efficiently with the Cooper&Hunter Exterior Architectural Grille, protecting the coils at the back of your PTAC unit to help maintain proper air flow into and out of the unit.



AB-PTGRL

## Ceiling Cassette Panel

The 4-Way Mini Split Ceiling Cassette Front Display Panel may be used to operate the unit if the remote control has been misplaced or inoperable.

### CH-NPNL09-18CT

Grill	in	16.5x16.5x0.78
Panel Dimension (WxDxH)	in	25.47x25.47x1.97

### CH-NPNL24-48CT

Grill	in	24.49x24.49x1
Panel Dimension (WxDxH)	in	37.4x37.4x2.17



# AHRI CERTIFICATION

AHRI Certified Reference Number	Outdoor Unit Model Number	Indoor Model Number(s)
215864254	CH-R18MES-230VO	
215864255	CH-R18MES-230VO	
215864256	CH-R18MES-230VO	
215864257	CH-R28MES-230VO	
215864258	CH-R28MES-230VO	
215864259	CH-R28MES-230VO	
215864260	CH-R36MES-230VO	
215864261	CH-R36MES-230VO	
215864262	CH-R36MES-230VO	
215864263	CH-R48MES-230VO	
215864264	CH-R48MES-230VO	
215864265	CH-R48MES-230VO	
215864269	CH-RVHP19M-230VO	
215864270	CH-HVPR19M-230VO	
215864271	CH-HVPR19M-230VO	
215864272	CH-HVPR28M-230VO	
215864273	CH-HVPR28M-230VO	
215864274	CH-HVPR28M-230VO	
215864275	CH-HVPR36M-230VO	
215864276	CH-HVPR36M-230VO	
215864277	CH-HVPR36M-230VO	
215864278	CH-HVPR48M-230VO	
215864279	CH-HVPR48M-230VO	
215864280	CH-HVPR48M-230VO	
215864266	CH-R60MES-230VO	
215864267	CH-R60MES-230VO	
215864268	CH-R60MES-230VO	
215864281	CH-RVHP55M-230VO	
215864282	CH-RVHP55M-230VO	
215864283	CH-RVHP55M-230VO	
215864266	CH-R60MES-230VO	
215864267	CH-R60MES-230VO	
215864268	CH-R60MES-230VO	
215864144	CH-RES06-115VO	CH-R060LVWM-115VI
215864145	CH-RES09-115VO	CH-R090LVWM-115VI
215864157	CH-RES09-115VO	CH-RB090LVWM-115VI
215864147	CH-RES09-230VO	CH-R09MOLVWM-230VI
215864159	CH-RES09-230VO	CH-RB09MOLVWM-230VI
215864168	CH-RES09-230VO	CH-PRO09MASTWWM-230VI
215864184	CH-RES09-230VO	CH-RH09MASTWWM-230VI
215864194	CH-RES09-230VO	CH-RSH09-12MCT
215864206	CH-RES09-230VO	CH-RH09MCT
215864223	CH-RES09-230VO	CH-RS09MDT-MS
215864225	CH-RES09-230VO	CH-RS06-12MDT-MS
215864248	CH-RES09-230VO	CH-RSH06-12MCT1W
215864235	CH-RES09-230VO	CH-RSH09MMC
215864146	CH-RES12-115VO	CH-R120LVWM-115VI
215864158	CH-RES12-115VO	CH-RB120LVWM-115VI
215864148	CH-RES12-230VO	CH-R12MOLVWM-230VI
215864160	CH-RES12-230VO	CH-RB12MOLVWM-230VI
215864169	CH-RES12-230VO	CH-PRO12MASTWWM-230VI
215864185	CH-RES12-230VO	CH-RH12MASTWWM-230VI
215864195	CH-RES12-230VO	CH-RSH09-12MCT
215864207	CH-RES12-230VO	CH-RH12MCT
215864224	CH-RES12-230VO	CH-RS12MDT-MS
215864226	CH-RES12-230VO	CH-RS06-12MDT-MS
215864249	CH-RES12-230VO	CH-RSH06-12MCT1W
215864236	CH-RES12-230VO	CH-RSH12MMC
215864149	CH-RES18-230VO	CH-R18MOLVWM-230VI
215864161	CH-RES18-230VO	CH-RB18MOLVWM-230VI
215864170	CH-RES18-230VO	CH-PRO18MASTWWM-230VI
215864186	CH-RES18-230VO	CH-RH18MASTWWM-230VI
215864196	CH-RES18-230VO	CH-RSH18MCT
215864208	CH-RES18-230VO	CH-RH18MCT
215864227	CH-RES18-230VO	CH-RS18MDT-MS
215864250	CH-RES18-230VO	CH-RSH18MCT1W
215864237	CH-RES18-230VO	CH-RSH16MMC
215864238	CH-RES18-230VO	CH-RSH18MFC
215864150	CH-RES24-230VO	CH-R24MOLVWM-230VI
215864162	CH-RES24-230VO	CH-RB24MOLVWM-230VI
215864171	CH-RES24-230VO	CH-PRO24MASTWWM-230VI

AHRI Certified Reference Number	Outdoor Unit Model Number	Indoor Model Number(s)
215864187	CH-RES24-230VO	CH-RH24MASTWWM-230VI
215864197	CH-RES24-230VO	CH-RSH24MCT
215864209	CH-RES24-230VO	CH-RH24MCT
215864228	CH-RES24-230VO	CH-RS24MDT-MS
21528018	CH-HPR35-230VO	CH-35HASTWWM-230V
215864239	CH-RES24-230VO	CH-RSH24MFC
215864151	CH-RHP06F9-230VO	CH-R06MOLVWM-230VI
215864163	CH-RHP06F9-230VO	CH-RB06MOLVWM-230VI
215864172	CH-RHP06F9-230VO	CH-PRO06MASTWWM-230VI
215864178	CH-RHP06F9-230VO	CH-RH06MASTWWM-230VI
215864212	CH-RHP06F9-230VO	CH-RS06MDT-MS
215864215	CH-RHP06F9-230VO	CH-RS06-12MDT-MS
215864251	CH-RHP06F9-230VO	CH-RSH06-12MCT1W
215864152	CH-RHP09-230VO	CH-R09MOLVWM-230VI
215864164	CH-RHP09-230VO	CH-RB09MOLVWM-230VI
215864173	CH-N48LCU-230VO	CH-48AHU
208141208	CH-NHPR48LCU-230VO	CH-48AHU
205263864	CH-HYP48LCUO	CH-48LCUO/1
207742342	CH-N48LCU-230VO	CH-48LCUO/1
207742350	CH-NHPR48LCU-230VO	CH-48LCUO/1
205263865	CH-HYP48LCUO	CH-48LCFC/1
207742343	CH-N48LCU-230VO	CH-48LCFC/1
207742351	CH-NHPR48LCU-230VO	CH-48LCFC/1
208141206	CH-N60LCU-230VO	CH-60AHU
211246029	CH-NHPR60LCU-230VO	CH-60AHU
207742344	CH-N60LCU-230VO	CH-60LCUO/1
210665987	CH-HPR06F9-230VO	CH-B06MOLVWM-230VI
210665988	CH-E509-230VO	CH-B09MOLVWM-230VI
210665992	CH-HPR09-230VO	CH-B09MOLVWM-230VI
210665985	CH-E509-115VO	CH-B090LVWM-115VI
210665989	CH-E512-230VO	CH-B12MOLVWM-230VI
210665993	CH-HPR12-230VO	CH-B12MOLVWM-230VI
210665986	CH-E512-115VO	CH-B120LVWM-115VI
210665990	CH-E518-230VO	CH-B18MOLVWM-230VI
210665994	CH-HPR18-230VO	CH-B18MOLVWM-230VI
210665991	CH-E524-230VO	CH-B24MOLVWM-230VI
210665995	CH-HPR24-230VO	CH-B24MOLVWM-230VI
215864173	CH-RHP09-230VO	CH-PRO09MASTWWM-230VI
215864179	CH-RHP09-230VO	CH-RH09MASTWWM-230VI
215864188	CH-RHP09-230VO	CH-RSH09-12MCT
215864200	CH-RHP09-230VO	CH-RH09MCT
215864213	CH-RHP09-230VO	CH-RS09MDT-MS
215864216	CH-RHP09-230VO	CH-RS06-12MDT-MS
215864252	CH-RHP09-230VO	CH-RSH06-12MCT1W
215864232	CH-RHP09-230VO	CH-RSH09MMC
215864153	CH-RHP12-230VO	CH-R12MOLVWM-230VI
215864165	CH-RHP12-230VO	CH-RB12MOLVWM-230VI
215864174	CH-RHP12-230VO	CH-PRO12MASTWWM-230VI
215864180	CH-RHP12-230VO	CH-RH12MASTWWM-230VI
215864189	CH-RHP12-230VO	CH-RSH09-12MCT
215864201	CH-RHP12-230VO	CH-RH12MCT
215864214	CH-RHP12-230VO	CH-RS12MDT-MS
215864217	CH-RHP12-230VO	CH-RS06-12MDT-MS
215864253	CH-RHP12-230VO	CH-RSH06-12MCT1W
215864233	CH-RHP12-230VO	CH-RSH12MMC
215864154	CH-RHP18-230VO	CH-R18MOLVWM-230VI
215864166	CH-RHP18-230VO	CH-RB18MOLVWM-230VI
215864175	CH-RHP18-230VO	CH-PRO18MASTWWM-230VI
215864181	CH-RHP18-230VO	CH-RH18MASTWWM-230VI
215864190	CH-RHP18-230VO	CH-RSH18MCT
215864202	CH-RHP18-230VO	CH-RH18MCT
215864218	CH-RHP18-230VO	CH-RS18MDT-MS
215864243	CH-RHP18-230VO	CH-RSH18MFC
215864234	CH-RHP18-230VO	CH-RSH16MMC
215864155	CH-RHP24-230VO	CH-R24MOLVWM-230VI
215864167	CH-RHP24-230VO	CH-RB24MOLVWM-230VI
215864176	CH-RHP24-230VO	CH-PRO24MASTWWM-230VI
215864182	CH-RHP24-230VO	CH-RH24MASTWWM-230VI
215864191	CH-RHP24-230VO	CH-RSH24MCT
215864203	CH-RHP24-230VO	CH-RH24MCT
215864219	CH-RHP24-230VO	CH-RS24MDT-MS

AHRI Certified Reference Number	Outdoor Unit Model Number	Indoor Model Number(s)
215864244	CH-RHP24-230VO	CH-RSH24MFC
215864156	CH-RHP35-230VO	CH-R33HOLVWM-230VI
215864177	CH-RHP35-230VO	CH-PRO33HASTWWM-230VI
215864183	CH-RHP35-230VO	CH-RH33HASTWWM-230VI
215864192	CH-RHP36LCU-230VO	CH-RSH36LCCT
215864204	CH-RHP36LCU-230VO	CH-RH36LCCT
215864220	CH-RHP36LCU-230VO	CH-RS36LCDT-MS
215864245	CH-RHP36LCU-230VO	CH-RSH36LCFC
215864193	CH-RHP48LCU-230VO	CH-RSH48LCCT
215864205	CH-RHP48LCU-230VO	CH-RH48LCCT
215864221	CH-RHP48LCU-230VO	CH-RS48LCDT-MS
215864246	CH-RHP48LCU-230VO	CH-RSH48LCFC
215864222	CH-RHP60LCU-230VO	CH-RS60LCDT-MS
215864247	CH-RHP60LCU-230VO	CH-RSH60LCFC
215864269	CH-RVHP19M-230VO	CH-PRO06MASTWWM-230VI
215864270	CH-RVHP19M-230VO	CH-RS06MDT-MS
215864271	CH-RVHP19M-230VO	CH-RS06MDT-MS
215864272	CH-RVHP28M-230VO	CH-PRO06MASTWWM-230VI
215864273	CH-RVHP28M-230VO	CH-RS06MDT-MS
215864274	CH-RVHP28M-230VO	CH-RS06MDT-MS
215864275	CH-RVHP36M-230VO	CH-PRO06MASTWWM-230VI
215864276	CH-RVHP36M-230VO	CH-RS06MDT-MS
215864277	CH-RVHP36M-230VO	CH-RS06MDT-MS
215864278	CH-RVHP48M-230VO	CH-PRO09MASTWWM-230VI
215864279	CH-RVHP48M-230VO	CH-RS09MDT-MS
215864280	CH-RVHP48M-230VO	CH-RS09MDT-MS
215864281	CH-RVHP55M-230VO	CH-PRO06MASTWWM-230VI
215864282	CH-RVHP55M-230VO	CH-RS06MDT-MS
215864283	CH-RVHP55M-230VO	CH-RS06MDT-MS
215864120	CH-PQ18-230VO	CH-PQ18AHU
215864121	CH-PQ24-230VO	CH-PQ24AHU
215864122	CH-PQ33-230VO	CH-PQ33AHU
215864123	CH-PQ36-230VO	CH-PQ36AHU
215864125	CH-PQ55-230VO	CH-PQ55AHU
215864284	CH-R36LCU-230VO	CH-RS36LCAHU
215864134	CH-R48LCU-230VO	CH-RS48LCAHU
215864285	CH-R60LCU-230VO	CH-RS60LCAHU
215864133	CH-REL30-230VO	CH-RS30MAHU
215864131	CH-RES18-230VO	CH-RS18MAHU
215864132	CH-RES24-230VO	CH-RS24MAHU
215864126	CH-RHP18-230VO	CH-RS18MAHU
215864127	CH-RHP24-230VO	CH-RS24MAHU
215864128	CH-RHP36LCU-230	




# COOPER&HUNTER's PRO-TECH DEALER PROGRAM

## Cooper&Hunter introduces you to our NEW Pro-Tech Dealer Program 2025

available to HVAC contractors and technicians, and focuses on recognizing and promoting growth to our top members.

*Stand out from your competition and earn exclusive benefits, including up to 3 additional years of Warranty for the Cooper&Hunter systems.*

### 3 CATEGORIES YOU MAY QUALIFY FOR:



20 SYSTEMS\* / YEAR



50 SYSTEMS\* / YEAR



100 SYSTEMS\* / YEAR



# COOPER&HUNTER's COMMERCIAL PRO-TECH PROGRAM



### Benefits include:

- Priority Customer Service Phone Line
- Preferred Locator placement on Cooper&Hunter's website
- Marketing Material and Co-branding
- Educational Material
- \$500 Voucher for VRF Training by Cooper&Hunter Engineers
- Invitations to exclusive sponsorship events by Cooper&Hunter and partners
- Points earned to use on Cooper&Hunter's online store
- Travel expenses paid with invitation to Cooper&Hunter's annual HQ meeting



# MINI URBAN VRF


SERIES




For questions on VRF Commercial Solutions, contact us at  
[vrf@cooperandhunter.us](mailto:vrf@cooperandhunter.us)



**CH**  
Cooper & Hunter



TV AD



TV AD



**NASCAR**



TV AD

**WE CREATE EMOTIONS TOGETHER**

cooperandhunter.us